#### Presented By: **Candela Corporation** (800) 922-9226

Contact Phone: Contact E-mail: sales@candelacorp.com



GE Lighting

# 18635 - 100PAR/HIR/SP10

# GE PAR38


• Up to 42% more efficient than standard halogen Up to 27% energy savings

• Up to 60% longer life -4000 hours


# a product of

# ecomagination<sup>-</sup>

Energy Savings







#### **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

#### Warning

Risk of Electric Shock

- Turn power off before inspection, installation or removal.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.
- Risk of Burn
- Allow lamp to cool before handling.
- Risk of Fire
- Keep combustible materials away from lamp.

**Customer Name:** Project Name: Fixture Type:

## **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base Filament Wattage Voltage Rated Life

Halogen - PAR PAR38 Medium Skirt (E26/50x39) CC-8 100 120 3000 hrs

### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens 2030 Center Beam Candlepower 30000 (CBCP) Color Temperature 2900 K Nominal Initial Lumens per Watt 20

### DIMENSIONS

Maximum Overall Length (MOL) Bulb Diameter (DIA) Bulb Diameter (DIA) (MAX) 5.3130 in(135.0 mm) 4.750 in(120.6 mm) 4.750 in(120.6 mm)

### **PRODUCT INFORMATION**

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168906371