

S28716

100W/LED/HID/5000K/277-347V/EX39 100 watt - LED HID Replacement; 5000K; Mogul extended base; 277-347 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 277 347V
 UL approved for totally enclosed fixtures
 Damp location IP65 rated
 For outdoor & indoor use

- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C
- · Safety chain included

Additional Technical Specifications

- Operating Frequency 50-60Hz
- Working Voltage AC 250-380V
- Power Factor >0.9

Minimum Compartment Size							
Length	Width	Depth					
17.3 inch	9.25 inch	9.25 inch					

Optional accessory: In-line surge protector 80-935



S28716

Item Number	Product Line	UPC	UPC Voltage		Incandesce Equivalen		Fluorescent Equivalent		HID Equivalent	
S28716	Hi-Pro	045923287169	277-347	100	500W		150W		400W	
Base	ANSI Base	Lamp Code		Di	Dimmable/Non- Dimmable Finish		MOL In Inches	MOD I		
Mogul Extended	EX39		100W/LED/HID/5000K/277- 347V/EX39			White	9-5/8"	5.87"	13300	

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type
------------------------	----------------	-------	-----	--------------------	-----------------------	------	--------------

50000	5000	Natural Light	80+	300	-20C (-4F) to a maximum of +65C (+149F)		4	Вох	
DLC ID:		RoHS Complian	t	UL Classification		Warranty	Thermal	Thermal Management	
PLVV0A6LDCRO DLC Search		Yes	C	:ULus - Wet Loca	tion Rated	5 Year Limited	More [Details About	