

LED OMNIDIRECTIONAL A-LAMP

A19, A21 SERIES



7w, 10w

12w

17w



7w, 10w

12w

17w

PRODUCT DESCRIPTION:

MaxLite's versatile, ENERGY STAR®-qualified LED Omnidirectional A-Line lamps replicate true A19 and A21 incandescents with a 300-degree beam angle that produces even light in all directions. They are suited to a wide variety of residential and commercial applications, including chandeliers, pendants, wall sconces and table and floor lamps. The 7-, 10-, 12- and 17-watt lamps replace 40-, 60-, 75- and 100-watt incandescent bulbs, respectively, and yield more than 80 percent savings in energy. LED Omnidirectional A-Line lamps are dimmable down to 10 percent on a wide variety of dimming control systems. They are offered in a standard medium base, which enables convenient screw-in, as well as GU24-base installation into existing lamps and fixtures that are used for both residential and commercial applications.

FEATURES:

- 25,000 hour life (L70 standards)
- CRI: 82
- Dimmable down to 10 percent
- Saves more than 80 percent on energy
- Power factor: > .9
- Standard E26 base & GU24 base
- Five year limited warranty

APPLICATIONS

- Chandeliers
- Pendants
- Table and floor lamps
- Sconces
- Not for use in fully enclosed luminaires
- Suitable for use in damp locations

MODEL SELECTION (Full list of order codes on pg. 3)

Typical order example: 10A19DLED27

		DLED		
FAMILY	BASE	DIMMABILITY	COLOR RENDERING INDEX (CRI)*	CCT
7A19= 7 watts, A19 10A19= 10 watts, A19 12A19= 12 watts, A19 17A21= 17 watts, A21	(OMIT)= E26 GU= GU24	DLED= Dimmable	(OMIT)= 82 9= 90+	27= 2700K 30= 3000K 41= 4100K

COMPATIBLE DIMMERS:

MAKE	DIMMER MODEL	MAKE	DIMMER MODEL
Lutron	CTCL-153P	Leviton	IPL06
Lutron	DVCL-153P	Leviton	IP110
Lutron	LGCL-153P	Leviton	6631-LW
Lutron	S-600	Leviton	6683-IW

NOTES:

1. * 90+ CRI available in 3000K only

ORDERING:

ORDER CODE	MODEL	WATTS	EQUIVALENCY	OUTPUT (LUMENS)	DIMENSIONS	CCT
E26 Base						
73612*	7A19DLED27	7	40	470	2.50" x 4.40"	2700K
73613*	7A19DLED30	7	40	470	2.50" x 4.40"	3000K
73614	7A19DLED41	7	40	470	2.50" x 4.40"	4100K
73581*	10A19DLED27	10	60	800	2.50" x 4.40"	2700K
73615**	10A19DLED30	10	60	800	2.50" x 4.40"	3000K
73616	10A19DLED41	10	60	800	2.50" x 4.40"	4100K
73582*	12A19DLED27	12	75	1100	2.50" x 4.40"	2700K
73617	12A19DLED30	12	75	1100	2.50" x 4.40"	3000K
73618	12A19DLED41	12	75	1100	2.50" x 4.40"	4100K
73583*	17A21DLED27	17	100	1600	2.74" x 5.06"	2700K
73619**	17A21DLED30	17	100	1600	2.74" x 5.06"	3000K
73620	17A21DLED41	17	100	1600	2.74" x 5.06"	4100K
E26 Base 90+ CRI						
73708**	12A19DLED930	12	60	800	2.50" x 4.40"	3000K
GU24 Base						
73621*	7A19GUDLED27	7	40	470	2.50" x 4.38"	2700K
73622*	7A19GUDLED30	7	40	470	2.50" x 4.38"	3000K
73623	7A19GUDLED41	7	40	470	2.50" x 4.38"	4100K
73624*	10A19GUDLED27	10	60	800	2.50" x 4.38"	2700K
73625*	10A19GUDLED30	10	60	800	2.50" x 4.38"	3000K
73626	10A19GUDLED41	10	60	800	2.50" x 4.38"	4100K
73627*	12A19GUDLED27	12	75	1100	2.50" x 4.38"	2700K
73628*	12A19GUDLED30	12	75	1100	2.50" x 4.38"	3000K
73629	12A19GUDLED41	12	75	1100	2.50" x 4.38"	4100K
73630*	17A21GUDLED27	17	100	1600	2.74" x 4.90"	2700K
73631*	17A21GUDLED30	17	100	1600	2.74" x 4.90"	3000K
73632	17A21GUDLED41	17	100	1600	2.74" x 4.90"	4100K
GU24 Base 90+ CRI						
74026**	12A19GUDLED930	12	60	800	2.50" x 4.38"	3000K

*ENERGY STAR qualified

**ENERGY STAR pending

Please contact your MaxLite representative to order products that don't have order codes listed here.