

## LED OMNIDIRECTIONAL A-LAMP

### A19 GEN 5 SERIES



6W, 9W & 11W



15W



GU24 Base



## PRODUCT DESCRIPTION:

MaxLite's LED Omnidirectional A-Line lamp replicate true A19 incandescents. They are suited to a wide variety of residential and commercial applications, including pendants, wall sconces and table and floor lamps.

## FEATURES:

- 6W, 480lm, 40W Inc. replacement
- 9W, 800lm, 60W Inc. replacement
- 11W, 1100lm, 75W Inc. replacement
- 15W, 1600lm, 100W Inc. replacement
- Dimmable down to 10 percent
- Power factor:  $\geq 0.90$
- 25,000 hour life (L70 standards)
- CRI:  $\geq 80$
- ENERGY STAR Certified
- Standard E26 base
- Suitable for dry and damp locations
- Not for use in fully enclosed luminaires
- Five year limited warranty

## APPLICATIONS

- Pendants
- Table and floor lamps
- Sconces

## ORDERING:

| MODEL SELECTION (Full list of order codes on pg. 2)                                                                 |                                       | Typical order example: 9A19DLED27/G5 |                                                          |                          |
|---------------------------------------------------------------------------------------------------------------------|---------------------------------------|--------------------------------------|----------------------------------------------------------|--------------------------|
|                                                                                                                     |                                       | DLED                                 |                                                          |                          |
| FAMILY                                                                                                              | BASE                                  | DIMMABILITY                          | CCT                                                      | GENERATION               |
| <b>6A19=</b> 6 watts, A19<br><b>9A19=</b> 9 watts, A19<br><b>11A19=</b> 11 watts, A19<br><b>15A19</b> 15 watts, A19 | <b>(OMIT)=</b> E26<br><b>GU=</b> GU24 | <b>DLED=</b> Dimmable                | <b>27=</b> 2700K<br><b>30=</b> 3000K<br><b>40=</b> 4000K | <b>/G5=</b> Generation 5 |

### NOTES:

1. 6A19DLED27/G5 is available in bulk pack (50pcs)
2. 9A19DLED27/G5 is available in 4-Packs and bulk pack (50pcs)
3. 11A19DLED27/G5 is available in bulk pack (50pcs)

**SPECIFICATIONS:**

|                     |                         | 6A19DLEDxx/G5             | 9A19DLEDxx/G5 | 11A19DLEDxx/G5 | 15A19DLEDxx/G5 |
|---------------------|-------------------------|---------------------------|---------------|----------------|----------------|
| ITEM                | SPECIFICATION           | DETAILS                   |               |                |                |
| GENERAL PERFORMANCE | Power Consumption       | 6W                        | 9W            | 11W            | 15W            |
|                     | Lumens Delivered        | 480                       | 800           | 1100           | 1600           |
|                     | Efficacy (lm/w)         | 80                        | 88            | 100            | 106            |
|                     | CRI                     | ≥80                       |               |                |                |
|                     | Color Temperature (CCT) | 2700K, 3000K, 4000K       |               |                |                |
|                     | Lumen Maintenance (L70) | 25,000 Hours              |               |                |                |
| ELECTRICAL          | Power Factor            | ≥0.9                      |               |                |                |
|                     | Input Voltage           | 120V                      |               |                |                |
| PHYSICAL            | Base Type               | E26                       |               |                |                |
|                     | Operating Temperature   | -4°F - 104°F              |               |                |                |
| CERTIFICATION       | Certification           | UL Listed, RoHS Compliant |               |                |                |
|                     | Environment             | Dry, Damp                 |               |                |                |
|                     | Warranty                | 5 Year Limited            |               |                |                |

Lighting layouts and spacing criteria available upon request

**ORDERING:**

| ORDER CODE      | MODEL             | ENERGY STAR | WATTS | EQUIVALENCY | DELIVER LUMENS | EFFICACY (lm/W) | CRI | CCT   | DIMENSIONS (W" x MOL") |
|-----------------|-------------------|-------------|-------|-------------|----------------|-----------------|-----|-------|------------------------|
| <b>E26 Base</b> |                   |             |       |             |                |                 |     |       |                        |
| 107589          | 6A19DLED27/G5     | ★           | 6     | 40W Inc.    | 480            | 80              | 80  | 2700K | 2.36" x 4.25"          |
| 107590          | 6A19DLED27/G5/BP  | ★           | 6     | 40W Inc.    | 480            | 80              | 80  | 2700K |                        |
| 107718          | 6A19DLED30/G5     | ★           | 6     | 40W Inc.    | 480            | 80              | 80  | 3000K |                        |
| 107584          | 9A19DLED27/G5     | ★           | 9     | 60W Inc.    | 800            | 88              | 82  | 2700K |                        |
| 107809          | 9A19DLED27/G5/4P  | ★           | 9     | 60W Inc.    | 800            | 88              | 82  | 2700K |                        |
| 107583          | 9A19DLED27/G5/BP  | ★           | 9     | 60W Inc.    | 800            | 88              | 82  | 2700K |                        |
| 107717          | 9A19DLED30/G5     | ★           | 9     | 60W Inc.    | 800            | 88              | 82  | 3000K |                        |
| 107585          | 11A19DLED27/G5    | ★           | 11    | 75W Inc.    | 1100           | 100             | 83  | 2700K |                        |
| 107586          | 11A19DLED27/G5/BP | ★           | 11    | 75W Inc.    | 1100           | 100             | 83  | 2700K |                        |
| 107719          | 11A19DLED30/G5    | ★           | 11    | 75W Inc.    | 1100           | 100             | 83  | 3000K |                        |
| 1408351         | 11A19DLED40/G5    | ★           | 11    | 75W Inc.    | 1100           | 100             | 83  | 4000K | 2.36" x 4.61"          |
| 107720          | 15A19DLED27/G5    | ★           | 15    | 100W Inc.   | 1600           | 106             | 84  | 2700K |                        |
| 107721          | 15A19DLED30/G5    | ★           | 15    | 100W Inc.   | 1600           | 106             | 84  | 3000K |                        |

★ ENERGY STAR Certified

Specifications are subject to change without notice.

| ORDER CODE       | MODEL            | ENERGY STAR | WATTS | EQUIVALENCY | DELIVER LUMENS | EFFICACY (lm/W) | CRI | CCT   | DIMENSIONS (W" x MOL") |
|------------------|------------------|-------------|-------|-------------|----------------|-----------------|-----|-------|------------------------|
| <b>GU24 Base</b> |                  |             |       |             |                |                 |     |       |                        |
| 1409336          | 6A19GUDLED27/G5  | ☆           | 6     | 40W Inc.    | 480            | 80              | 80  | 2700K | 2.36" x 4.21"          |
| 1409407          | 6A19GUDLED30/G5  | ☆           | 6     | 40W Inc.    | 480            | 80              | 80  | 3000K |                        |
| 1409337          | 6A19GUDLED40/G5  | ☆           | 6     | 40W Inc.    | 480            | 80              | 80  | 4000K |                        |
| 1409408          | 9A19GUDLED27/G5  | ☆           | 9     | 60W Inc.    | 800            | 89              | 80  | 2700K |                        |
| 1409338          | 9A19GUDLED30/G5  | ☆           | 9     | 60W Inc.    | 800            | 89              | 80  | 3000K |                        |
| 1409243          | 9A19GUDLED40/G5  | ☆           | 9     | 60W Inc.    | 800            | 89              | 80  | 4000K |                        |
| 1409339          | 11A19GUDLED27/G5 | ☆           | 11    | 75W Inc.    | 1100           | 100             | 80  | 2700K |                        |
| 1409340          | 11A19GUDLED30/G5 | ☆           | 11    | 75W Inc.    | 1100           | 100             | 80  | 3000K |                        |
| 1409019          | 11A19GUDLED40/G5 | ☆           | 11    | 75W Inc.    | 1100           | 100             | 80  | 4000K |                        |
| 1409341          | 15A19GUDLED27/G5 | ☆           | 15    | 100W Inc.   | 1600           | 106             | 83  | 2700K | 2.36" x 4.61"          |
| 1409342          | 15A19GUDLED30/G5 | ☆           | 15    | 100W Inc.   | 1600           | 106             | 83  | 3000K |                        |
| 1409245          | 15A19GUDLED40/G5 | ☆           | 15    | 100W Inc.   | 1600           | 106             | 83  | 4000K |                        |

☆ ENERGY STAR Pending

**COMPATIBLE DIMMERS (6A19DLEDXX/G5):**

| MANUFACTURE | DIMMER MODEL    |
|-------------|-----------------|
| AH          | SDM/600         |
|             | SDM3/1000       |
| ALMOND      | LUXDM600-12     |
| CTL         | DM600-12-3      |
| GE          | 18024           |
| LEVITON     | 603-6631-A      |
|             | 6631            |
|             | 6631-A          |
|             | 6631-LA         |
|             | 6672            |
|             | 6683            |
|             | 6683-10Z        |
|             | IPI06-1LZ       |
|             | IPI10-1LZ       |
|             | IPL06           |
| LUTRON      | AYCL-153P-WH    |
|             | AYCL-153PH      |
|             | DVCL-153P-WH    |
|             | DVWCL-153PH-WHC |
|             | S-603PH-WH      |
|             | SCL-153PH-WH    |
|             | TGCL-153PH-WH   |
| MAAXIMA     | MEW-DM600       |

**COMPATIBLE DIMMERS (9A19DLEDXX/G5):**

| MANUFACTURE | DIMMER MODEL    |
|-------------|-----------------|
| AH          | SDM/600         |
|             | SDM3/1000       |
| ALMOND      | LUXDM600-12     |
| CTL         | DM600-12-3      |
| GE          | 18024           |
| LEVITON     | 6631            |
|             | 6672            |
|             | 6683            |
|             | 603-6631-A      |
|             | 6631-A          |
|             | 6683-10Z        |
|             | IPI06-1LZ       |
|             | IPI10-1LZ       |
|             | IPL06           |
| LUTRON      | AYCL-153P-WH    |
|             | AYCL-153PH      |
|             | DVCL-153P-WH    |
|             | DVWCL-153PH-WHC |
|             | S-603PH-WH      |
|             | SCL-153PH-WH    |
|             | TGCL-153PH-WH   |
| MAAXIMA     | MEW-DM600       |

**COMPATIBLE DIMMERS (11A19DLEDXX/G5):**

| MANUFACTURE | DIMMER MODEL    |
|-------------|-----------------|
| AH          | SDM/600         |
|             | SDM3/1000       |
| ALMOND      | LUXDM600-12     |
| CTL         | DM600-12-3      |
| GE          | 18024           |
| LEVITON     | 6631            |
|             | 6672            |
|             | 6683            |
|             | 603-6631-A      |
|             | 6631-A          |
|             | 6631-LA         |
|             | 6683-10Z        |
|             | IPI06-1LZ       |
|             | IPI10-1LZ       |
| LUTRON      | IPL06           |
|             | AYCL-153P-WH    |
|             | AYCL-153PH      |
|             | DVCL-153P-WH    |
|             | DVWCL-153PH-WHC |
|             | S-603PH-WH      |
|             | SCL-153PH-WH    |
|             | TGCL-153PH-WH   |
| MAAXIMA     | MEW-DM600       |

**COMPATIBLE DIMMERS (15A19DLEDXX/G5):**

| MANUFACTURE | DIMMER MODEL   |
|-------------|----------------|
| AH          | SDM/600        |
|             | SDM3/1000      |
| ALMOND      | LUXDM600-12    |
| CTL         | DM600-12-3     |
| GE          | 18024          |
| LEVITON     | 6631           |
|             | 603-6631-A     |
|             | 6631-A         |
|             | 6631-LA        |
| LUTRON      | AYCL-153P-WH   |
|             | AYCL-153PH     |
|             | D-600PH-DK     |
|             | D-600R-IV      |
|             | DV-600P-WH     |
|             | DV-600PH-WH    |
|             | DV-603P        |
|             | DV-603PH-WH    |
|             | DV-603PR       |
|             | DVW-600PH-WH   |
|             | MACL-153M-WH   |
|             | MACL-153MLH-WH |
|             | MACL-153MR-WH  |
|             | MACL-153MH-WH  |
|             | S-600          |
|             | S-600-AL       |
|             | S-600P-WH      |
|             | S-603PH-WH     |
|             | TG-600PH-IV    |
|             | TGCL-153PH-WH  |