



T8

14.5T8/MAS/48-835/MF20/P 10/1

Philips MainsFit (UL Type B) MasterClass T8 LED tubes with industry leading reliability, shatter-prevention and lifetime. The UL Type B LED tubes are designed with easy installation and long-term maintenance simplicity in mind. Upgrade your lighting to MasterClass and realize 70,000 hour LED lifetime backed by a 7-year, full replacement limited warranty.


Product data

General information			
Base	G13 [Medium Bi-Pin Fluorescent]	Lamp Current (Min)	54 mA
EU RoHS compliant	Yes	Wattage Equivalent	32 W
Nominal Lifetime (Nom)	70000 h	Starting Time (Nom)	0.5 s
Switching Cycle	50000	Warm Up Time to 60% Light (Nom)	0.5 s
Tier	MasterClass	UL Type	Type B - bypass the ballast
Light technical		Power Factor (Nom)	0.9
Color Code	835 [CCT of 3500K]	Voltage (Nom)	120-277 V
Beam Angle (Nom)	180 °	Temperature	
Initial lumen (Nom)	2000 lm	T-Ambient (Max)	113 °F
Color Designation	White (WH)	T-Ambient (Min)	-4 °F
Correlated Color Temperature (Nom)	3500 K	T-Storage (Max)	149 °F
Luminous Efficacy (rated) (Nom)	137.00 lm/W	T-Storage (Min)	-40 °F
Color Consistency	<6	T-Case Maximum (Nom)	158 °F
Color Rendering Index (Nom)	80	Controls and dimming	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Dimmable	Limited
Operating and electrical		Mechanical and housing	
Input Frequency	50 to 60 Hz	Bulb Finish	Frosted
Power (Rated) (Nom)	14.5 W	Bulb Material	Plastic
Lamp Current (Max)	125 mA	Product Length	48 in

Bulb Shape	Tube, double-ended
Approval and application	
Energy Saving Product	Yes
Approbation Marks	RoHS compliance UL certificate DLC compliance
Product data	
Order product name	14.5T8/MAS/48-835/MF20/P 10/1

EAN/UPC - Product	046677575526
Order code	575522
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002325534
Net Weight (Piece)	0.265 lb
Model Number	9290023255


Dimensional drawing




14.5T8/MAS/48-835/MF20/P 10/1

Product	D1	D2	A1	A2	A3
14.5T8/MAS/48-835/MF20/P 10/1	1-1/16 in	1-1/8 in	47-3/16 in	47-1/2 in	47-3/4 in

Photometric data




LEDtube_G13_835-POC



LEDtube_G13_1-LDD



Photometric data




Catalytic Performance 4.5	Philips Lighting B.V.	Page 17
---------------------------	-----------------------	---------

LEDtube_14.5W_G13_835-GUL


Lifetime



LEDtube_70K_1_LumenVsTc-LMP




Life Expectancy Diagram



LEDtube_70K_LifetimeVsTc-LED

LEDtube_70K_FailureRate-LED

Lifetime



Lumen Maintenance Diagram

