

Presented By: Candela Corporation
Contact Phone: 800-922-9226
Contact E-mail: sales@candelacorp.com

Customer Name:
Project Name:
Fixture Type:



GE
Lighting

18617 - 1946

GE T3 - Aircraft; Low Voltage



CAUTIONS & WARNINGS

Caution

- Risk of Burn
 - Allow lamp/fixture to cool before handling.

Warning

- Lamp emits UV radiation which may cause eye/skin irritation.
 - Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Fire
 - Keep combustible materials away from lamp.
 - Use in fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 - Dispose of lamp in a closed container.
 - Do not exceed rated voltage.
 - Do not touch glass with bare hands.
 - Do not turn on lamp until fully installed.
 - Do not use lamp if outer glass is scratched or broken.
 - Keep children away.
 - Use eye protection when handling lamp.
 - Use protective screen when handling.

GENERAL CHARACTERISTICS

Lamp Type	Miniature - T & TL Shape
Bulb	T3
Base	2-Pin with Leads
Filament	CC-6
Rated Life (NOM)	50.0 h
Bulb Material	Quartz
Atmosphere	Gas-filled
Primary Application	Aircraft;Low Voltage

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	8294.0
Nominal Initial Lumens per Watt (NOM)	33.176
Mean Spherical Candlepower (MSCP) (NOM)	660.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	250.0
Voltage (NOM)	28.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	1.460 in(37.1 mm)
Bulb Diameter (DIA) (NOM)	0.375 in(9.5 mm)
Light Center Length (LCL) (NOM)	0.870 in(22.1 mm)

PRODUCT INFORMATION

Product Code	18617
Description	1946
ANSI Code	1946
Standard Package	Case
Standard Package GTIN	10043168186176
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard	10
Package	
UPC	043168186179