

Day-Brite

CFI

by  Signify

Recessed

FluxPanel

interact
ready.



Experience a good deal

Day-Brite / CFI FluxPanel luminaires set the stage
for affordability and lasting quality



The unfailing choice for lasting confidence

Investing in quality pays off in the long run.

- Help bolster wellbeing and productivity without worrying about flicker and other undesired effects.
- Immerse users in comfortable, welcoming spaces that are free of glare and distractions; with color that remains consistent across luminaires and over time.
- Protect both the integrity of electrical equipment and overall building efficiency from the effects of total harmonic distortion.
- Rely on one flat panel LED luminaire family for multiple applications - recessed, surface, or suspended.

Affordable doesn't have to mean cheap



Why risk the unknown, and your reputation, for the sake of short-term savings?

FluxPanel luminaires are specially designed to keep your budget on track, and unlike others, we don't stop there. Backed by more than 125 years of lighting expertise, each low-profile, dimmable LED luminaire imparts confidence and peace of mind for you and those in the space.

Reliable Signify drivers offer dependable and lasting performance, while the low glare surface gradient creates uniform light distribution.

FluxPanel luminaires are well-suited for office, healthcare and educational facilities that seek to minimize hassles, meet sustainability goals, and maximize return on investment.

When a good deal matters, put your trust in FluxPanel luminaires. Visit www.day-brite.com.

FXP FluxPanel LED

Ordering guide

Example: 2FXP38L840-2-DS-UNV-DIM-EMLED7

Width	Family	Nominal delivered lumens	Color	Length	Diffuser	Voltage	Driver	Options ⁶	
	FXP		—	—	DS —	—	—		
1 1'	FXP	Standard configurations¹	835 80 CRI, 3500K 840 80 CRI, 4000K	2 2' 4 4'	DS Diffuse (smooth)	UNV Universal Voltage, 120-277 volt 120³ 120V 277³ 277V 347 347V	DIM⁴ 0-10V dimming SDIM³ Step dimming to 40% input power XDIM^{3,5} MarkX phase dimming	F1 3/8" flex, 3 wire 18 gauge 6' F2 3/8" flex, 4 wire 18 gauge 6' F1/D 3/8" twin flex, 3 wire 18 gauge 6' for dimmable luminaires F2/SW 3/8" single flex, 5 wire 18 gauge 6' for dimmable luminaires F2/GW 3/8" single flex, 6 wire 18 gauge 6' for dimmable and emergency luminaires GLR Fusing, fast blow EMLED Bodine BSL310 10W battery pack EMLED7 Bodine BSL17 7W battery pack CHIC Chicago Plenum rated IAP⁷ Integral Interact Pro RF sensor, enables network lighting control	
2 2'									
		Base configurations²							
		2x2 38B 3800 lumens 2x4 42B 4200 lumens 1x4 38B 3800 lumens							

Accessories (order separately)

- **FMA22** – 2'x2' "F" mounting frame for NEMA "F" mounting
- **FSK22** – 2'x2' surface mount field installation kit (factory welded seams)
- **FSF22** – 2'x2' surface mount field assembly kit (field assembled)
- **FMA24** – 2'x4' "F" mounting frame for NEMA "F" mounting
- **FSK24** – 2'x4' surface mount field installation kit (factory welded seams)
- **FSF24** – 2'x4' surface mount field assembly kit (field assembled)
- **FMA14** – 1'x4' "F" mounting frame for NEMA "F" mounting
- **FSK14** – 1'x4' surface mount field installation kit (factory welded seams)
- **FSF14** – 1'x4' surface mount field assembly kit (field assembled)
- **2PCH48-1-SC** – adjustable cable hanger kit for 2x2 with straight white 18/3 cord (two-1 powered, 1 non-powered)
- **2PCH48-1D-SC** – adjustable cable hanger kit for 2x2 with straight white 18/5 cord for dimming (two-1 powered, 1 non-powered)
- **4PCH48-1-SC** – adjustable cable hanger kit for 1x4 or 2x4 with straight white 18/3 cord (two-1 powered, 1 non-powered)
- **4PCH48-1D-SC** – adjustable cable hanger kit for 1x4 or 2x4 with straight white 18/5 cord for dimming (two-1 powered, 1 non-powered)

Footnotes

- 1 Standard configurations are packaged one unit per carton
- 2 Base configurations are packaged two units per carton, and sold in even quantities only
- 3 XDIM requires 120V or 277V specification
- 4 0-10v dimming to 1% for Standard, and 5% for Base configurations
- 5 2x4 available with 54L package or lower
- 6 All options available with Standard configurations only
- 7 Available with DIM driver option only

Standard configurations (1 unit/carton) available with all choices, unless otherwise noted. Base configurations (2 units/carton, order in even quantities) selections indicated by blue.

Signify drivers provide reliable performance for peace of mind.



FluxPanel luminaires are Designlights Consortium® qualified. Please see the DLC QPL list for exact catalog numbers (<http://www.designlights.org/QPL>).

The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract.

