



WORLDWIDE PARTNER

[site search](#)[home](#)[products](#)[education / resources](#)

Commercial Products & Solutions

[lighting applications](#)[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)[Products](#) > 26143**26143 – 305**

GE S8 - Aircraft; Low Voltage

GENERAL CHARACTERISTICS

Lamp type	Miniature - S Shape
Bulb	S8
Base	Single Contact Bayonet (BA15s)
Filament	C-2V
Wattage	14
Voltage	28
Voltage (MIN)	300
Rated Life	300 hrs
Rated Life (MIN)	14 hrs
Rated Life (Hor)	14 hrs
Rated Life (Vert)	300 hrs
Bulb Material	Lead glass
Atmosphere	Gas-filled
Primary Application	Aircraft; Low Voltage

PHOTOMETRIC CHARACTERISTICS


Initial Lumens	188
Initial Lumens (Hor)	13.42857
Initial Lumens (Vert)	188
Nominal Initial Lumens per Watt	13
Center Beam Candlepower (CBCP)	188
Mean Spherical Candlepower (MSCP)	15

DIMENSIONS

Maximum Overall Length (MOL)	2.0000 in (50.8 mm)
Bulb Diameter (DIA)	1.000 in (25.4 mm)
Light Center Length (LCL)	1.120 in (28.4 mm)

PRODUCT INFORMATION


Product Code	26143
Description	305



Bulb



Base

[PRINT](#)[View Larger](#)**ADDITIONAL RESOURCES**[Catalogs](#)[Disposal Policies & Recycling Information](#)

ANSI Code	305
Standard Package Case	
Standard Package GTIN	00043168261432
Standard Package Quantity	50
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	50
UPC	043168963688

NOTES

- Filament: Supported

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2009