



WORLDWIDE PARTNER

[site search](#)[home](#)[products](#)[education / resources](#)

Commercial Products & Solutions

[lighting applications](#)[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)[Products](#) > 26255**26255 – 356**

GE G3.5 (G3 1/2) - Aircraft; Low Voltage

GENERAL CHARACTERISTICS

Lamp type	Miniature - G Shape
Bulb	G3.5 (G3 1/2)
Base	Miniature Bayonet (Ba9s)
Filament	C-2F
Wattage	5
Voltage	28
Voltage (MIN)	500
Rated Life	500 hrs
Rated Life (MIN)	5 hrs
Rated Life (Hor)	5 hrs
Rated Life (Vert)	500 hrs
Bulb Material	Lead glass
Atmosphere	Vacuum
Primary Application	Aircraft; Low Voltage

PHOTOMETRIC CHARACTERISTICS


Initial Lumens	44
Initial Lumens (Hor)	8.8
Initial Lumens (Vert)	44
Nominal Initial Lumens per Watt	8
Center Beam Candlepower (CBCP)	44
Mean Spherical Candlepower (MSCP)	3.5

DIMENSIONS


Maximum Overall Length (MOL)	0.9400 in (23.8 mm)
Bulb Diameter (DIA)	0.438 in (11.1 mm)
Light Center Length (LCL)	0.500 in (12.7 mm)

PRODUCT INFORMATION

Product Code	26255
Description	356
ANSI Code	356



Bulb



Filament

[View Larger](#)**ADDITIONAL RESOURCES**[Catalogs](#)[Disposal Policies & Recycling Information](#)

Standard Package Case

Standard Package 00043168262552

GTIN

Standard Package 50

Quantity

Sales Unit	Unit
------------	------

No Of Items Per	1
-----------------	---

Sales Unit

No Of Items Per	50
-----------------	----

Standard Package

UPC	043168963428
-----	--------------

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2009