



WORLDWIDE PARTNER

[site search](#)[home](#)[products](#)[education / resources](#)

Commercial Products & Solutions

[lighting applications](#)[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)[Products](#) > 38918**38918 – 400**

GE T3.25 (T3 1/4) - Low Voltage

GENERAL CHARACTERISTICS

Lamp type	Miniature - T & TL Shape
Bulb	T3.25 (T3 1/4)
Base	Wedge (W2.1x9.5d)
Filament	C-2F
Wattage	3
Voltage	28
Voltage (MIN)	1000
Rated Life	1000 hrs
Rated Life (MIN)	3 hrs
Rated Life (Hor)	3 hrs
Rated Life (Vert)	1000 hrs
Atmosphere	Vacuum
Primary Application	Low Voltage

PHOTOMETRIC CHARACTERISTICS


Initial Lumens	20
Initial Lumens (Hor)	6.666667
Initial Lumens (Vert)	20
Nominal Initial Lumens per Watt	6
Center Beam Candlepower (CBCP)	20
Mean Spherical Candlepower (MSCP)	1.6

DIMENSIONS


Maximum Overall Length (MOL)	1.0600 in (26.9 mm)
Bulb Diameter (DIA)	0.406 in (10.3 mm)
Light Center Length (LCL)	0.560 in (14.2 mm)

PRODUCT INFORMATION


Product Code	38918
Description	400
ANSI Code	400
Standard Package	Case



Bulb



Base



Filament

[View Larger](#)**ADDITIONAL RESOURCES**[Catalogs](#)[Disposal Policies & Recycling Information](#)

Standard Package	20043168389185
GTIN	
Standard Package	50
Quantity	
Sales Unit	Unit
No Of Items Per	1
Sales Unit	
No Of Items Per	50
Standard Package	
UPC	043168389181

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2009