

Presented By: Candela Corporation

Contact Phone: 800-922-9226

Contact E-mail: sales@candelaCorp.com

Customer Name:

Project Name:

Fixture Type:



GE
Lighting

46887 - GE saf-t-gard® 40 watt A15 2-pack

40A15CF/STGPQ2/6

- ➡ Add a decorative touch by using GE Crystal Clear bulbs in chandeliers, sconces or anywhere the bulb is visible.
- ➡ These GE Decorative Saf-T-Gard bulbs are ideal for ceiling fans.
- ➡ Smaller, better-fitting bulb makes them less visible in fixture than regular bulbs
- ➡ Rugged filament withstands fan vibration.
- ➡ 120 volts
- ➡ 2600K soft white light appearance
- ➡ Estimated yearly energy costs \$4.82 based on 3 hours per day \$0.11 per kWh
- ➡ GE saf-t-gard® bulbs feature a protective Teflon® coating that helps contain glass fragments if broken. Designed with heavy-duty, all-weather construction, these bulbs protect against shattering, rain breakage and splatter from oil and lubricants. GE saf-t-gard® bulbs are perfect for home use in kitchens, basements garages, workshops and enclosed exterior fixtures
- ➡ Lasts 1.4 years based on 3 hours per day usage
- ➡ A15 shape with medium base for use in rough service applications

Product Photo



GENERAL CHARACTERISTICS

Base Description	Medium Screw
Base Type	Screw-In
Filament	C-9
Rated Life Hours-nominal	1500 h
Primary Application	Shatter-Resistant Ceiling Fan
Product Technology	Incandescent
Base	E26
Bulb Shape	A15

PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt	10
Initial Lumens-nominal	355 lm
Color Temperature	2600 K

PRODUCT INFORMATION

Product Code	46887
Description	40A15CF/STGPQ2/6
Alternative Unit Of Measure	BUNDLE
Standard Package Quantity	60
Ean UPC	043168461597
Standard Package GTIN	00043168468879
No Of Items Per Sales Unit	2
No Of Items Per Standard Package	60
Sales Unit	Unit
UCC	043168468879

DIMENSIONS

Diameter	1.875 in
----------	----------

ELECTRICAL CHARACTERISTICS

Wattage	40 W
Input Voltage [nom]	120 V