



GE
Lighting

WORLDWIDE PARTNER

[site search](#)

» [home](#)

» [products](#)

» [education / resources](#)

Commercial Products & Solutions

» [lighting applications](#)

[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)

[Products](#) > 40176

40176 – 4460X

GE PAR36 - Tractor

GENERAL CHARACTERISTICS

Lamp type	Sealed Beam - PAR
Bulb	PAR36
Base	3 Screw Terminals
Filament	C-6/C-6
Product Technology	Incandescent
Wattage	40/40.001
Voltage	12.8/12.8001
Rated Life	320 hrs/320 hrs
Primary Application	Tractor

PHOTOMETRIC CHARACTERISTICS

Beam Spread - Horizontal	22.001° - 10 %
Beam Spread - Vertical	13° - 10 %
Max. Beam	0
Candlepower (MBCP) (MAX)	

DIMENSIONS

Maximum Overall Length (MOL)	2.7500 in (69.8 mm)
Bulb Diameter (DIA)	4.500 in (114.3 mm)

PRODUCT INFORMATION

Product Code	40176
Description	4460X
ANSI Code	4460X
Standard Package	Case
Standard Package GTIN	00043168401760
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168961837



Base



Filament



[View Larger](#)

ADDITIONAL RESOURCES

[Catalogs](#)

[Disposal Policies & Recycling Information](#)

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)

[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2009