

Model Number AC-42CD700UV-QS AC-42CD700AQBCC


Input Voltage: 120-277V
Input Frequency: 50/60Hz
Side and Bottom Mount/Leads Options

**MULTI-
CURRENT SWITCHING
AND DIMMING**

ELECTRICAL SPECIFICATIONS:

Output Power Max.	Input Power	Input Current	Minimum PF (full load)	Max. THD (full load)	Output Voltage	Output Current	T case Max.	Minimum Starting Temp.	Efficiency Up To	Dimming Protocol	Dimming Range
42W	52W @ 120V 51W @ 277V	0.44A @ 120V 0.175A @ 277V	>0.95	<20%	35-60V	700mA±5%	90° C	-40° C	82%	0 to 10V	10 to 100%
31W	38W @ 120V 37W @ 277V	0.33A @ 120V 0.14A @ 277V	>0.95	<20%	35-60V	530mA±5%	90° C	-40° C	83%	0 to 10V	10 to 100%
24W	30W @ 120V 29W @ 277V	0.25A @ 120V 0.11A @ 277V	>0.95	<20%	35-60V	410mA±5%	90° C	-40° C	83%	0 to 10V	10 to 100%
21W	26W @ 120V 25W @ 277V	0.22A @ 120V 0.09A @ 277V	>0.95	<20%	35-60V	350mA±5%	90° C	-40° C	83%	0 to 10V	10 to 100%



WIRING:



Lead Lengths

Black	5.9"	Blue	5.9"	Purple	5.9"
White	5.9"	Red	5.9"	Gray	5.9"

PHYSICAL:



Bottom Mount Option
Model Number:
AC-42CD700AQBCC

Dimensions

Length	6.5"	Mounting Length	5.9"
Width	2.9"	Weight	0.83 lbs.
Height	1.18"	Case Qty.	40 pcs.

SAFETY & PERFORMANCE:

- UL US Class 2
- cUL LVLE
- UL Outdoor Type I
- Class A sound rating
- No PCBs
- Open/Short Circuit Protection
- LED driver has a life expectancy of 50,000 hours at Tcase of ≤75°C
- LED driver has a life expectancy of 100,000 hours at Tcase of ≤65°C
- Warranty: 5 yrs based on max case temp of <75°C; 3 yrs based on max case temp of 90°C*
- Input/Output Isolation
- FCC Title 47 CFR Part 15
- Surge Protection (2 KV)

INSTALLATION:

- LED drivers shall be installed inside electrical enclosures
- 18 AWG 600V/105C tinned strand copper lead-wires are required for installation
- Max Remote installation distance is 18 ft
- LED driver cases should be grounded



*AC Electronics/AC LED Power Designs warrants to the purchaser that each LED Driver will be free from defects in material or workmanship for a period of 5 years when operated at max case temp of up to <75°C; 3 years from date of manufacture when operated at a max case temp of up to 90°C when properly installed and under normal conditions of use. See aceleds.com for complete warranty policy.



Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

