

LED Retrofit Kit + Housing For Decorative Wall Pack

Contains LED Retrofit Kit and LED Lighting Housing



Made In USA



AC Electronics LED Retrofit Kit + Housing vs. Standard HID Lights

Wall Pack Light Source	Input Wattage	Lifespan Hrs/Yrs	Energy Use (24hrs/day) Annual	Annual Cost (maintenance + electricity) @ \$0.11/kWh	Electrical Cost Savings
HID	165	24,000/ 2.7	1446 kWh	\$159.00	
LED	35	50,000/ 5.7	307 kWh	\$33.74	79%


Kit Model Number AC302/36/350 6

— Includes Grandlite® Housing SM302 —

Includes:

- **Two-Output Channel, Class 2 LED Driver, Model Number: AC-D18C350UVH**
- **2 PCB LED Arrays with 28 Cree MX-6 LEDs mounted to industrial grade aluminum LED Driver bracket**
- **Instructions for Installation**
- **All Required Assembly and Mounting Hardware**
- **Grandlite® SM302 Lighting Housing**

Wiring Diagram



Warranty

LED Retrofit Kit + Housing warranty is only valid when it is used in the Grandlite® fixture it was designed to be used in unless otherwise approved in writing by AC Electronics. Any other use in any other fixture assembly or use with non-AC specified or supplied components will void this warranty.

*AC warrants to the purchaser that this LED Retrofit Kit + Housing will be free from defects in material or workmanship for a period of 5 years from date of manufacture, when operated at a maximum ambient temperature of 110°F or 45°C, when properly installed and under normal conditions of use.

See www.aceleds.com for complete warranty policy.

Grandlite® is a registered trademark of Grandlite® International Corporation. AC Electronics is not associated with Grandlite® international.

Tork® 2107 Photocell

Approved For Use With AC LED Retrofit Kits

- 120/277V 1800 VA Ballast Load
- 1 To 5 FC Turn On Light Level
- 3 To 15 FC Turn Off Light Level
- SPST Switch
- 16 AWG 6 Inch Wire Lead Terminal
- Temperature Rating
-40 to 140°F
- 1/2" Conduit Mounting
- Not included, available
from secondary sources



Specifications

Item	Specification
Input Voltage	120-277V, 50/60Hz
LED CRI	75
Fixture CRI	74
LED Color Temperature	5000K
Fixture Color Temperature	5410
Fixture Lumens	2637 Lumen
Kit Lumens Outside Fixture	3501 Lumen
Lumen Maintenance	≥70% @ 5 years
Fixture Efficacy	75 Lumen/Watt
Zonal Lumen Requirement	0-90°; 100% 80-90° <10%
Warranty	5 years*
LED Quantity (Brand: Cree MX-6)	28
LED TMP Temperature @25°C	61°C
Input Power	35W
Driver Efficiency	88%
Power Factor @277V	0.999
THD @277V	8%
Driver TMP temp @25°C Ambient	56°C
Noise	<24dB
EMI	FCC part 15
Max Operating Temperature	45°C Ambient
Min Operation Temperature	-40°C
LED Retrofit Kit Dimensions / Weight	2"H x 17"W x 7"D / 3 lbs.
Assembled Fixture Dimensions / Weight	7.1"H x 18.1"W x 9.25"D / 12 lbs.



A division of AC Electronics

Note: LM79 and ies files are available upon request.

Note: All specifications refer to the installed kit.