


# DOUBLE-ENDED SUPER HIGH PRESSURE SODIUM



## L/W BASE

Watts (W)	Ordering Code	Lamp Description	PAR (MMOL/S)	Color Temp (K)	Operating Current	Max. Starting Current	Average Life (h)	MOL (MM)	Burn Position
750	5002494	AHS-DE750W/Pro-Plus	1450	2100	3.6A	7.0A	10,000	323	Horizontal
		System Voltage	Lamp Voltage	Ignition Voltage	Warm Up Time	Reignition Time	Bulb Type	Dia. (MM)	Ballast
		400V	210V	3200V	7 minutes	2 minutes	T10	30	HPS 750W Electronic

Watts (W)	Ordering Code	Lamp Description	PAR (MMOL/S)	Color Temp (K)	Operating Current	Max. Starting Current	Average Life (h)	MOL (MM)	Burn Position
600	5003285	AHS-DE600W/Pro-Plus	1150	2100	3.2A	7.0A	10,000	323	Horizontal
		System Voltage	Lamp Voltage	Ignition Voltage	Warm Up Time	Reignition Time	Bulb Type	Dia. (MM)	Ballast
		400V	180V	2440V	7 minutes	2 minutes	T10	30	HPS 600W Electronic

 contains mercury  
contient du mercure



Manage in Accord with Disposal Laws  
[www.lamprecycle.org](http://www.lamprecycle.org) 1-800-895-8842

**⚠ CALIFORNIA PROPOSITION 65 WARNING:** These products can expose you to Mercury known to the state of California to cause birth defects or other reproductive harm. For more information, please go to: [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

## R - NON SELF-EXTINGUISHING LAMP

**WARNING:** This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Complies with the USA Federal Standard 21 CFR 1040.30 and Canada Standard SOR/80-381.