

B239PUNV-D

APPLICATION and PERFORMANCE SPECIFICATION

Description:

Electronic ballast for (1/2) **F39T5HO** or (2) **F24T5HO** or (2) **FT36W/2G11** lamps

- Line Voltage: 120 - 277 vac, $\pm 10\%$, 50/60Hz
- Series Lamp Operation
- Auto Reset after Lamp Replacement

- Programmed Rapid Start
- Active Power Factor Correction
- End of Lamp Life Shutdown Circuitry

Model	Line Volts	No. of Lamps	Lamp Type	Input Watts	Nominal Line Amps	Ballast Factor	Power Factor	Harmonic Total	Crest Factor
B239PUNV-D	120	2	F39T5HO	89	0.75	1.00	> 0.98	< 10%	< 1.7
	120	1	F39T5HO	47	0.39	1.10	> 0.98	< 10%	< 1.7
	277	2	F39T5HO	88	0.32	1.00	> 0.98	< 10%	< 1.7
	277	1	F39T5HO	47	0.18	1.10	> 0.95	< 10%	< 1.7
	120	2	F24T5HO	59	0.51	1.15	> 0.98	< 10%	< 1.7
	277	2	F24T5HO	59	0.22	1.15	> 0.95	< 10%	< 1.7
	120	2	FT36W/2G11	71	0.59	0.97	> 0.98	< 10%	< 1.7
	277	2	FT36W/2G11	70	0.26	0.97	> 0.95	< 10%	< 1.7

Application and Performance Specification Information Subject to Change without Notification.

Performance:

- Meets ANSI Standard C82.11-1993
- Meets ANSI Standard C62.41-1991
- Meets FCC Part 18 (Class A) for EMI and RFI Non-Consumer Limits

Safety:

- No PCB's
- UL listed (Class P, Type 1 Outdoor)
- CSA Certified

Application:

- Minimum Starting Temperature: 0 °F, -18 °C
- Maximum Ambient Temperature: 104 °F, 40 °C
- Maximum Case Temperature(tc): 167 °F, 75 °C
- Sound Rating: Class A
- Remote Mounting: 18 ft.
- Wire Trap, Plug-in Connectors are Standard
- Leadwire Option Available

Physical Parameters

- | | Inches | Metric |
|---------------------------------------|-----------------------|----------|
| • Mounting Length: (Center to Center) | 16.28" +/- 0.010" | 413.5 mm |
| • Overall Length: | 16.88" +/- 0.010" | 428.8 mm |
| • Width: | 1.18" + 0.03"/- 0.02" | 30 mm |
| • Height: | 1.00" + 0.04"/- 0.01" | 25.4 mm |
| • Weight: | 1.25 lbs | 0.6kg |
| • Carton Quantity: | 10 pieces | |

Warranty:

Universal Lighting Technologies warrants to the purchaser that each electronic ballast will be free from defects in material or workmanship for a period of 5 years from date of manufacture when properly installed and under normal conditions of use. Call **1-800-BALLASTx800** for technical assistance.

Manufactured in North America

