


4

3

DWG NO. 1000096 SH 1

1

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED



- NOTES:
1. ALL DIMENSIONS ARE IN MM.
 2. SEAL TEMP: SHOULD BE MAINTAINED BELOW 350°C
 3. THE DIMENSIONS AND SPECIFICATIONS OF PRODUCT LISTED IN THIS SHEET ARE SUBJECT TO CHANGE WITHOUT NOTICE FOR IMPROVEMENT.

CHARACTERISTICS	
VOLTAGE	120 V
WATTAGE	2000 W
COLOR TEMP.	3200 K
TOTAL LUMEN	57200 Lm
BASE TYPE	E39
AVERAGE LIFE	500 HRS
FILAMENT TYPE	CC-8
BURN POSITION	Any

ITEM	QTY	DESCRIPTION	CODE IDENT	PART NUMBER	REMARKS	
LIST OF MATERIALS						
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES DECIMALS .X ± - .XX ± - .XXX ± - ANGLES ± - DRILLED HOLES PER AND 10387 REMOVE BURRS AND SHARP EDGES ALL DIMENSIONS AFTER PLATING		CONTRACT NO.		USHIO AMERICA, INC. 5440 Cerritos Avenue Cypress, CA 90630		
		APPROVALS				DATE
		DRAWN	R.AMPARO	09/01/99	TITLE BWG JCV120V-2000W	
		CHKD	D.GILCZYNSKI	09/01/99		
		ENGR				
		MFG				
		QUAL				
MATERIAL COMPOSITE		DSGN ACTVY		SIZE	CODE IDENT NO.	DWG NO.
FINISH		GOVT ACTVY		B	BWG	1000096
				SCALE	WEIGHT	SHEET
				NONE		1 OF 1

4

3

1

2

1

CAD