

Product 24543

Number:

Order F40/D830/ECO

Abbreviation:

40W, T12 rapid start fluorescent lamp, Designer rare earth phosphor, 3000K color temperature, 80 CRI, General

Description: ECOLOGIC

Product Information	
Abbrev. With Packaging Info.	F40D830ECO 30/CS 1/SKU
Actual Length (in)	47.780
Actual Length (mm)	1213.61
Average Rated Life (hr)	20000
Base	Medium Bipin
Bulb	T12
Color Rendering Index (CRI)	80
Color Temperature/CCT (K)	3000
Diameter (in)	1.591
Diameter (mm)	40.40
Family Brand Name	Designer 800, Ecologic
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	3300
Mean Lumens at 25C	2970
Nominal Length (in)	48.000
Nominal Length (mm)	1219.20
Nominal Wattage (W)	40.00



Footnotes

- Average life rating at 12 hours operation per start is 28,800 hours.
 Average rated life is measured at 3 hours per start on 2-lamp, rapid start magnetic ballasts per IES recommended practice. Lamp life on single-lamp rapid start ballasts may be reduced.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer. The "RS" designation has been eliminated to simplify the ordering abbreviation.
- 40W Rapid Start Lamps may be used in starter operated fixtures designed for 40W preheat lamps. Life rating for preheat service is approximately 15,000 hours average.
- SYLVANIAECOLOGIC fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as nonhazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local & state regulations. For more information, please visit www.lamprecycle.org