



PHYSICAL DIMENSIONS

4" x 4" Core





WIRING DIAGRAM




CAPACITOR

Dry Type or Oil Oval



IGNITOR



Pulse Height (kV): 3.0 ~ 4.0

Pulse Width ($\geq \mu$ s): 1.3 @ 2.7kV

**2 YEAR WARRANTY FROM
DATE OF MANUFACTURE**

MAGNETIC HID BALLAST

Ballast Type	Magnetic Pulse Start	Circuit Type	CWA
Lamp	350W Metal Halide M131	Frequency	60Hz

ELECTRICAL SPECIFICATIONS

		Five Tap				
Input Voltage (V)		120	208	240	277	480
Line Current (A)	Operating	3.4	2.0	1.7	1.5	0.9
	Open Circuit	1.6	0.9	0.8	0.7	0.4
	Starting	2.0	1.2	1.0	0.9	0.5
Recommended Fuse		10	7	5	5	3
Input Voltage At Lamp Dropout		70	120	140	165	280
UL Class H 180°C Temp. Code		A	A	A	A	A
Nom. Open Circuit Voltage		266				
Input Power (W)		410				
Power Factor ($\geq$ %)		90				
Regulation ($\pm$ %)	Line Volts	10				
	Lamp Watts	10				
Min. Starting Temp		-20°F / -30°C				
Ballast Dimensions (inches)	A	2.32				
	B	4.40				
Ballast Net Weight (lbs)		12.2				
Lead Length (inches)		12				
Capacitor	Capacitance (μ F)	24				
	Min VAC Rating (V)	330				
Requires Ignitor Model		GMHR3				
Coil Material (Pri./ Sec.)		Cu / Al				

60 HZ. TEST PROCEDURES

Short Circuit Current (A)	Secondary	Min	2.8				
		Max	4.2				
	Input	Min	1.2	0.7	0.6	0.5	0.3
		Max	3.5	2.0	1.8	1.5	0.9
Open Circuit Voltage (V)		Min	254				
		Max	300				
High Potential Test (V)		1 Minute	2000				
		1 Second	2400				

REFERENCE LAMP DATA

	Test Range	ANSI Standard
Starting Current (A)		2.8 ~ 4.2
CCF	1.5	$\leq$ 1.8
OCV (V)	254 ~ 300	
Off Time (Sec.)	2.0	$\leq$ 2.3
Peak Current (A)	6.9	$\leq$ 8.0
Overshoot (V)	-11	$\leq$ 90
VSS (V)	276	$\geq$ 270

OPTIONAL FEATURES

(ADD SUFFIX FOR OPTIONS)

-WB	With welded bracket
-I	With ignitor
-DC	With dry film capacitor
-OC	With oil filled capacitor
-K	With distributor replacement kit (includes bracket, capacitor and ignitor as necessary)