



PHYSICAL DIMENSIONS

4 1/4" x 6" Core





WIRING DIAGRAM



CAPACITOR

Dry Type or Oil Oval



**2 YEAR WARRANTY FROM
DATE OF MANUFACTURE**

MAGNETIC HID BALLAST

Ballast Type	Magnetic Probe Start	Circuit Type	CWA
Lamp	1000W Metal Halide M47	Frequency	60Hz

ELECTRICAL SPECIFICATIONS

		Quad Tap			
Input Voltage (V)		120	208	240	277
Line Current (A)	Operating	9.2	5.3	4.6	4.0
	Open Circuit	5.5	3.2	2.8	2.5
	Starting	5.6	3.2	2.8	2.4
Recommended Fuse		20	15	10	10
Input Voltage At Lamp Dropout		70	130	150	180
UL Class H 180°C Temp. Code		D	C	C	C
Nom. Open Circuit Voltage		411			
Input Power (W)		1076			
Power Factor (≥ %)		90			
Regulation (± %)	Line Volts	10			
	Lamp Watts	10			
Min. Starting Temp		-20°F / -30°C			
Ballast Dimensions (inches)	A	3.01			
	B	4.92			
Ballast Net Weight (lbs)		18.9			
Lead Length (inches)		12			
Capacitor	Capacitance (µF)	24			
	Min VAC Rating (V)	480			
Requires Ignitor Model		N/A			
Coil Material (Pri./ Sec.)		Cu / Al			

60 HZ. TEST PROCEDURES

Short Circuit Current (A)	Secondary	Min	4.2				
		Max	6.5				
	Input	Min	3.2	1.9	1.6	1.4	
		Max	9.5	5.6	4.8	4.2	
Open Circuit Voltage (V)		Min	340				
		Max	460				
High Potential Test (V)		1 Minute	2000				
		1 Second	2400				

REFERENCE LAMP DATA

	Test Range	ANSI Standard
Starting Current (A)		4.2 ~ 6.5
CCF	1.5	≤ 1.8
OCV (V)	340 ~ 460	
di/dt (A/ms)	1.7	≥ 1.5
Off Time (Sec.)	2.1	≤ 2.5
Peak Current (A)	11.3	≤ 11.5
Overshoot (V)	20	≤ 100
VSS (V)	352	

OPTIONAL FEATURES

(ADD SUFFIX FOR OPTIONS)

-WB	With welded bracket
-I	With ignitor
-DC	With dry film capacitor
-OC	With oil filled capacitor
-K	With distributor replacement kit (includes bracket, capacitor and ignitor as necessary)