


ELECTRONIC BALLAST

IG130ELSK

- One Lamp
- Multi-Watt
- Small Case Size
- Lightweight
- Versatile
- Energy Saving



Features & Benefits

Wide lamp versatility, suitable for one F25T8, F25T12, F30T8, F30T12, *FC12T9(32W), *F32T8, *F34T12, *F40T8, *F40T10, or *F40T12 lamp

Class A Sound Rating

End of Lamp Life Protection

More efficient compared to standard magnetic ballasts

Lead wires do not interfere with mounting holes

Contains No PCBs

Eliminates strobing

Thermal potting

Metal enclosure

Rapid Start



RoHS
compliant

ASK ABOUT
ENERGY STAR

SPECIFICATIONS

• Operating Voltage: 120 VAC $\pm$ 10%

• Frequency: 50/60Hz

• Protection: Class P Inherent Thermal Protection

• Regulatory Approvals: UL, CUL Listed

• Min. Starting Temp: 0°F (-17.78°C)


* 32°F Min. Starting Temp

• Max. Case Temp: 158°F (75°C)


• Over Current: Fuse

• Type 1 Outdoor, Normal Power Factor

DIMENSIONS



WIRING DIAGRAM



Weight: 13 oz. Case Quantity: 40pcs Case Weight: 29 lbs Standard Lead Length: black/white-24" blue/red-34"

Line Voltage	Lamp Type	Line Current	Input Power	Power Factor	Crest Factor	Ballast Factor	THD Percent	Min Start Temp
120	★ F25T8	0.45	22.7	0.50	1.39	0.90	117.9	0°F
120	F25T12	0.45	26.8	0.50	1.54	1.01	116.2	0°F
120	F30T8	0.45	27.3	0.50	1.33	0.90	117.4	0°F
120	F30T12	0.45	27.6	0.50	1.50	0.91	117.3	0°F
120	★ F32T8	0.49	27.8	0.53	1.32	0.80	118.8	32°F
120	F34T12	0.46	27.9	0.50	1.50	0.81	117.5	32°F
120	F40T12	0.56	28.0	0.50	1.40	0.73	118.4	32°F