

QUARTZ / HALOGEN SOCKETS

Multi-Base

L80054

G4, G6.35, GY6.35, GX5.3, GZ4 quartz lamps, 18" leads



GU7 Socket

GU7

100W - 250V


6" leads 250 dg. C -bottom



Miniature Bi-Pin Quartz

A. L36T B. L32T

Ceramic bodies with Mica covers, 750W-250V, 18", 200° C lds



A.

B.

18ga. 200° 12" leads

L80051-406

Use with GX5.3 lamps



Mini-Can Lampholder

B. LW2

18" lds

500W-250V, leads SF-1 200°



Mini-Can Lampholder

LS4

1000W-250V, 8.5 Amps, screw shell copper alloy



Mini-Can Lampholder

LS25-F

1000W-250V, 8.5 Amps, 18 Ga. 200° C lds, 12" leads



Miniature Bi-Pin Quartz Lampholders

Single-Ended • Multi Base

L80054-500

Multi-Base miniature bi-pin quartz lampholder accepts all popular single-ended miniature quartz lamps, including G4, G6.35, GY6.35, GX5.3 (MR16), and GZ4 (MR11).



Mini-Bi-Pin Single Ended

L422

Use with GX5.3 lamp, 150W-300V, 6" leads



Ceramic Halogen Socket

L425

G4, G6.35 lamps, 65W-28V



Wedge-Base Ceramic Socket

L1562-100

Accepts T5 & T3-1/4, 37.5W-28V lamps



Ceramic G4 Bi-Pin Socket

L1563-100

High heat applications, 750W-250V, 9" leads 18ga., 200° C lds



L38T

100W-250V, base G5.3 & GX5.3, 4" lds



L422A

70W-125V, base G5.3 & GX5.3, 6" leads

2" Dia.



Halogen Holders for R7's

L424

silver plated contacts 4-11/16" contact to contact, 500W-250V, 200°



GU10 Line Voltage Sockets & Accesories

A. LB2581968

(parallel side leads)

B. LB2581969

(rear leads)

ceramic 5" 18awg twist & lock action screw mount

C. LB25919301

snap-on mounting cap 1/8 IP thread



A.



B.



C.

Mini-Bi-Pin Single Ended

A. L80050-403

(18" leads)

B. L80050-404

(36" leads)

Use with GX5.3 lamp, 750W-250V, 6"

