

Features & Benefits

- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long Life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Utilizes non-shunted(rapid start) sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- 5 Year Warranty
- Made of Glass



Commercial Grade **LED T8 Lamp**



Flex™
Internal Driver **LED T8 Lamp**

Specification Data

Order Code	Model No.	Length	Lamp Wattage	Input Voltage	CCT	Initial Lumens	CRI	Beam Angle	LPW	Life	Operating Temp.	DLC
	L48T8/835/18G-ID 48	18	18	120-277	3500	2200	83	325	115	50000	-20 ~ 40	Yes
	L48T8/840/18G-ID 48	18	18	120-277	4000	2200	83	325	115	50000	-20 ~ 40	Yes
	L48T8/850/18G-ID 48	18	18	120-277	5000	2200	83	325	115	50000	-20 ~ 40	Yes

Ordering Information

EXAMPLE: **L48T8/840/14G-ID**

L	48	T8	8	40	14 G	-	ID
Manufacturer's Code	Normal Length 48=48"	Lamp Shape T8=T8	CRI 8=>80	CCT 50=5000K 40=4000K 35=3500K	Wattage 14G=14W		Internal Driver

Wiring diagram



Copyright © 2014 ESPEN Technology Inc. All Rights Reserved

Espen Technology Inc. | 12257 Florence Ave. | Santa Fe Springs, CA 90670

Toll Free: (866) 933-7736 | Tel.: (562) 529-2938 | Fax: (562) 529-2978 | Email: info@espentech.com