

HP22627P

Ballast Type:	Electromagnetic
Input Voltage:	277VAC +5%,-10%
Input Frequency:	60 Hz.

Starting Method:	Preheat
Lamp Connection:	Parallel
Unit Color:	Black

Unit Weight:	2.93 lb.
Carton Quantity:	15
Skid Quantity:	480

ELECTRICAL SPECIFICATION:[illegible]

PERFORMANCE:

- Electromagnetic lead type ballast
- Preheat start
- Parallel operation
- High power factor
- Encased & potted
- Sound rated A
- Meets ANSI C82.1

APPLICATION:


- Maximum case temperature: 194°F/90°C
- Maximum ambient temperature: 104°F/40°C
- Minimum starting temperature: 25°F/-4°C
- Remote mounting: 10 ft.

SAFETY:

- UL listed (Class P, Type HL, Type 1 outdoor)
- CSA/C22.2 Certified
- Automatic reset thermal protector
- No PCB's
- RoHS Compliant


STYLE:

10



H	W	L	M	S
1 11/16	2 3/8	6 9/16	6	5/16
1.69	2.38	6.56	6.00	0.31
2.71 cm	6.03 cm	16.66 cm	15.24 cm	0.79 cm

WIRING DIAGRAM:



Standard lead lengths:

Side Leads

- | | | |
|--------------|------------|----------------|
| • Blk: 15" | • Wht: 15" | • Blu: (2) 15" |
| Bottom Leads | | |
| • Blk: 8" | • Wht: 8" | • Blu:(2) 8" |
| | | * 3/8" Strip |

WARRANTY

Robertson Worldwide warrants to the purchaser that this ballast will be free from defects in material or workmanship for a period of 2 years from date of manufacture when properly installed and under normal conditions of use.