

W189D

Wall Sconce



Features

Housing

Die-formed Cold-rolled Steel
 Finish Option: -62 Satin Nickel -30 Oil Rubbed Bronze

Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity
 LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Electrical

High Power Factor, Low THD

Lamp


Integrate LED Module, Color Temperature Option 3000K, 3500K, 4000K, 5000K
 Adjustable Multiple Color Temperature Model (-MCT) with 3000K, 3500K, 4000K

Certification

ETL/cETL Listed, Suitable for Damp Locations

Warranty

5 Years Limited Warranty on Driver and LED



LED Type

Model	Input Voltage	Input Wattage	LED CT Option	CRI	Lumen (TYP)	Finish/Shade	Dimension (H x W x D)	Energy Star
W189D-xxxxK	120V-277V	15W	3000K/3500K /4000K/5000K	>80	1300	Satin Nickel / Acrylic	16.0" x 5.0" x 3.8"	Yes
W189D-MCT	120V-277V	15W	3000K/3500K/4000K	>80	1300	Satin Nickel / Acrylic	16.0" x 5.0" x 3.8"	*

Note: * Energy Efficiency 92.9 lm/W Meets Energy Star Requirement