

PAR56 LED

PAR56 SP LED White Superia 2000lm

0060650



Product features

- Sylvania's PAR56 LED light sources provide a top class and professional finish to pools and water features, - Unique single-point light source for improved visual appearance, with advanced fresnel lens optics which deliver impressive light and colour uniformity, - Full PPS (Polyphenylsulphide) plastic body, very resistant material for use in plastic and metal fixtures against corrosion by chlorinated and salt water, - Unique sealing method guarantees IP68 water-tightness, - Low heat generation, - Remote control is an optional accessory. Lamps also function with ordinary switches, -Only for use with magnetic (not electronic) transformers, - European production delivers outstanding performance and quality



PRODUCT OVERVIEW

Product name	PAR56 SP LED White Superia 2000lm
Technology	LED
Watt (Rated) (W)	20
Cap/Base	N/A
Fixture rating	Enclosed
General application	Hospitality, Residential & Consumer, SPG
ETIM Class	EC001959
Warranty	3 years
Fixture luminous flux (lm)	2000
Luminous flux (lm)	2000
Correlated colour temperature (k)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	95
Photobiological Risk Group	RG1
Total power consumption (W)	20
Electrical protection	Class III
Dimmable	No
Dimming method	N/A
Average life (Nominal) (h)	25000
IP rating	IP68
IK rating	IK00
Product EAN number	5410288606507

DATA TABLE

General data

Product name	PAR56 SP LED White Superia 2000lm
Technology	LED
Watt (Rated) (W)	20
Cap/Base	N/A
Fixture rating	Enclosed

PAR56 LED

PAR56 SP LED White Superia 2000lm

0060650

General application	Hospitality, Residential & Consumer, SPG
ETIM Class	EC001959
Warranty	3 years

Optical data

Fixture luminous flux (lm)	2000
Luminous flux (lm)	2000
Correlated colour temperature (k)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Luminous Intensity (cd)	870
Beam Angle (°)	95
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	20
Primary Supply/Product voltage - min (V)	12
Primary Supply/Product voltage - max (V)	12
Electrical protection	Class III
Dimmable	No
Dimming method	N/A
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50Hz

Lifetime data

Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

Physical data

IP rating	IP68
IK rating	IK00
Nominal Product Height (mm)	106
Nominal Product Diameter (mm)	176
Weight (kg)	0.552

Packaging

Product EAN number	5410288606507
Packaging single length / height (cm)	15.0
Packaging single width (cm)	15.0
Packaging single depth (cm)	16.3
DUN14 (outer)	15410288606504
Units per outer package	6
Packaging outer length / height (cm)	46.5
Packaging outer width (cm)	31.5
Packaging outer depth (cm)	18.3

PAR56 LED

PAR56 SP LED White Superia 2000lm

0060650

Safety data

Dry applications use only

No

TECHNICAL DRAWINGS

