



- Surelite™ ballasts deliver higher ultraviolet lamp output
- Surelite™ ballasts are smaller and lighter
- Surelite™ ballasts save energy through higher efficiency
- Surelite™ ballasts are instant starting
- Surelite™ ballasts operate cooler for longer life
- Surelite™ ballasts provide silent operation
- Surelite™ ballasts eliminate “stroboscopic effect”
- Surelite™ ballasts are versatile...each operates a wide range of lamps

Surelite™ SPECIFICATIONS—SINGLE LAMP BALLASTS

| LAMP TYPE | NOMINAL LAMP CURRENT | LAMP SIZE RANGE | VOLTAGE | CYCLES | BALLAST NO. | CASE SIZE |
|--------------|----------------------|-----------------|---------|--------|-------------|---|
| Preheat | 425 mA | 8" - 34" | 120 | 50/60 | 10-0054C* | 6 ³ / ₈ " x 2 ¹ / ₂ " x 1 ³ / ₄ " |
| Preheat | 425 mA | 8" - 34" | 220-240 | 50/60 | 10-0053C* | 6 ³ / ₈ " x 2 ¹ / ₂ " x 1 ³ / ₄ " |
| Slimline | 425 mA | 12" - 64" | 120 | 50/60 | 10-0034C* | 6 ³ / ₈ " x 2 ¹ / ₂ " x 1 ³ / ₄ " |
| Slimline | 425 mA | 12" - 64" | 220-240 | 50/60 | 10-0035C* | 6 ³ / ₈ " x 2 ¹ / ₂ " x 1 ³ / ₄ " |
| Cold Cathode | 100 mA | 12" - 48" | 120 | 50/60 | 10-0024B | 6 ³ / ₈ " x 2 ¹ / ₂ " x 1 ³ / ₄ " |
| Cold Cathode | 100 mA | 12" - 48" | 220-240 | 50/60 | 10-0025B | 6 ³ / ₈ " x 2 ¹ / ₂ " x 1 ³ / ₄ " |
| Cold Cathode | 50 mA | 12" - 48" | 120 | 50/60 | 10-0052B | 6 ³ / ₈ " x 2 ¹ / ₂ " x 1 ³ / ₄ " |
| Cold Cathode | 50 mA | 12" - 48" | 220/240 | 50/60 | 10-0059B | 6 ³ / ₈ " x 2 ¹ / ₂ " x 1 ³ / ₄ " |