



- Surelite™ ballasts deliver higher ultraviolet lamp output
- Surelite™ ballasts are smaller and lighter
- Surelite™ ballasts save energy through higher efficiency
- Surelite™ ballasts are instant starting
- Surelite™ ballasts operate cooler for longer life
- Surelite™ ballasts provide silent operation
- Surelite™ ballasts eliminate “stroboscopic effect”
- Surelite™ ballasts are versatile...each operates a wide range of lamps

## **Surelite™ SPECIFICATIONS—SINGLE LAMP BALLASTS**

LAMP TYPE	NOMINAL LAMP CURRENT	LAMP SIZE RANGE	VOLTAGE	CYCLES	BALLAST NO.	CASE SIZE
Preheat	425 mA	8" - 34"	120	50/60	10-0054C*	6 <sup>3</sup> / <sub>8</sub> " x 2 <sup>1</sup> / <sub>2</sub> " x 1 <sup>3</sup> / <sub>4</sub> "
Preheat	425 mA	8" - 34"	220-240	50/60	10-0053C*	6 <sup>3</sup> / <sub>8</sub> " x 2 <sup>1</sup> / <sub>2</sub> " x 1 <sup>3</sup> / <sub>4</sub> "
Slimline	425 mA	12" - 64"	120	50/60	10-0034C*	6 <sup>3</sup> / <sub>8</sub> " x 2 <sup>1</sup> / <sub>2</sub> " x 1 <sup>3</sup> / <sub>4</sub> "
Slimline	425 mA	12" - 64"	220-240	50/60	10-0035C*	6 <sup>3</sup> / <sub>8</sub> " x 2 <sup>1</sup> / <sub>2</sub> " x 1 <sup>3</sup> / <sub>4</sub> "
Cold Cathode	100 mA	12" - 48"	120	50/60	10-0024B	6 <sup>3</sup> / <sub>8</sub> " x 2 <sup>1</sup> / <sub>2</sub> " x 1 <sup>3</sup> / <sub>4</sub> "
Cold Cathode	100 mA	12" - 48"	220-240	50/60	10-0025B	6 <sup>3</sup> / <sub>8</sub> " x 2 <sup>1</sup> / <sub>2</sub> " x 1 <sup>3</sup> / <sub>4</sub> "
Cold Cathode	50 mA	12" - 48"	120	50/60	10-0052B	6 <sup>3</sup> / <sub>8</sub> " x 2 <sup>1</sup> / <sub>2</sub> " x 1 <sup>3</sup> / <sub>4</sub> "
Cold Cathode	50 mA	12" - 48"	220/240	50/60	10-0059B	6 <sup>3</sup> / <sub>8</sub> " x 2 <sup>1</sup> / <sub>2</sub> " x 1 <sup>3</sup> / <sub>4</sub> "