Presented By: Candela Corporation
Contact Phone: (800) 922-9226
Contact E-mail: sales@candelacorp.com

Customer Name: Project Name: Fixture Type:




GE Lighting

41459 - 100/300 6PK

GE Soft White PS25D

- Use original GE's Soft White when you need a light without glare and harsh shadows.
- Specifically designed for 3-way lamps in your home or office, GE 3-way bulbs offer a range of light levels. Choose the low light setting for energy savings, higher settings for general and activity lighting.
- Choose the low light setting for energy savings, higher settings for general and activity lighting.











CAUTIONS & WARNINGS

Warning

- Risk of Fire
- Use in fixture rated for this product.

GENERAL CHARACTERISTICS

Lamp Type Incandescent - A-line

Bulb PS25D

Base 3 Contact Mogul Screw

(E39D)

Filament CC-6
Bulb Finish Soft white
Wattage 100/200/300

Voltage 120
Rated Life 1200 hrs
Bulb Material Soft glass
Primary Application 3-Way

PHOTOMETRIC CHARACTERISTICS

Initial Lumens 1250 /2650 /3900 Nominal Initial Lumens per Watt 13 /13 /12

ELECTRICAL CHARACTERISTICS

Burn Position Universal burning position

DIMENSIONS

Maximum Overall Length 6.68 cm

(MOL)

Bulb Diameter (DIA) 3.125 cm Bulb Diameter (DIA) (MAX) 3.125 cm Light Center Length (LCL) 4.43 cm

PRODUCT INFORMATION

Product Code 41459
Description 100/300 6PK
Standard Package BUNDLE
Standard Package GTIN 00043168414593

Standard Package Quantity 30
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 30

Package

UPC 043168905053