



WORLDWIDE PARTNER

Commercial Products & Solutions

[site search](#)[home](#)[products](#)[education / resources](#)[lighting applications](#)[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)[Products](#) > 47800**47800 – 1003LL/BP2**

GE B6 - Automotive

GENERAL CHARACTERISTICS

Lamp type	Miniature - B Shape
Bulb	B6
Base	Single Contact Bayonet (BA15s)
Filament	C-6
Wattage	12
Voltage	12.8
Rated Life	400 hrs
Atmosphere	Gas-filled
Primary Application	Under Hood; Back up; Dome; Glove Box; High Mount Stop; Instrument, General; License Plate; Map; Step/Courtesy; Tail; Trunk/Cargo Area; Turn Signal, Rear

PHOTOMETRIC CHARACTERISTICS


Initial Lumens	189
Nominal Initial	15
Lumens per Watt	
Mean Spherical Candlepower (MSCP)	15

DIMENSIONS

Maximum Overall Length (MOL)	1.7500 in (44.4 mm)
Bulb Diameter (DIA)	0.750 in (19.0 mm)
Light Center Length (LCL)	1.060 in (26.9 mm)

PRODUCT INFORMATION


Product Code	47800
Description	1003LL/BP2
ANSI Code	1003
Standard Package Master	
Standard Package GTIN	50043168478002
Standard Package Quantity	48
Sales Unit	Blister



Bulb



Base



Filament



Package

[View Larger](#)**ADDITIONAL RESOURCES**[Catalogs](#)[Disposal Policies & Recycling Information](#)[Automotive Cross-Reference](#)

View a list of the vehicles that this bulb is compatible with by application, year, make, and model.

No Of Items Per 2
Sales Unit

No Of Items Per 96
Standard Package

UPC 043168478007

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2009