Presented By: **Candela Corporation** (800) 922-9226

Contact Phone: Contact E-mail: sales@candelacorp.com



GE Lighting

18633 - 100PAR/HIR/FL25 GE PAR38


• Up to 28% more efficient than standard halogen Up to 22% energy savings

• Up to 20% longer life -3000 hours


a product of

ecomagination⁻

Energy Savings







CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

- Do not use lamp if outer glass is scratched or broken.

Warning

Risk of Fire

- Keep combustible materials away from lamp.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.

Risk of Burn

- Allow lamp to cool before handling.
- Risk of Electric Shock

- Turn power off before inspection, installation or removal.

Customer Name: Project Name: Fixture Type:

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament Wattage Voltage Rated Life

Halogen - PAR PAR38 Medium Skirt (E26/50x39) CC-8 100/88 130/120 3000 hrs

PHOTOMETRIC CHARACTERISTICS

Initial Lumens 2030 /1470 Center Beam Candlepower 7000 (CBCP) Color Temperature 2900 K Nominal Initial Lumens per Watt 20 /16

DIMENSIONS

Maximum Overall Length (MOL) Bulb Diameter (DIA) Bulb Diameter (DIA) (MAX) 5.3130 in(135.0 mm) 4.750 in(120.6 mm) 4.750 in(120.6 mm)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168906388