#### Presented By: **Candela Corporation** Contact Phone: (800) 922-9226 Contact E-mail:



sales@candelacorp.com



# 10473 - 100PAR/HIR/FL40

# GE PAR38


• Up to 28% more efficient than standard halogen Up to 22% energy savings


• Up to 20% longer life -3000 hours

# a product of

# ecomagination<sup>--</sup>







### **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

### Warning

- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Burn
- Allow lamp to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.

**Customer Name:** Project Name: Fixture Type:

# **GENERAL CHARACTERISTICS**

Lamp Type
Bulb
Base
Filament
Wattage
Voltage
Rated Life

Halogen - PAR PAR38 Medium Skirt (E26/50x39) CC-8 100 120 3000 hrs

## **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens 2030 Center Beam Candlepower 3400 (CBCP) Color Temperature 2900 K Nominal Initial Lumens per Watt 20

### DIMENSIONS

Maximum Overall Length 5.3130 in(135.0 mm) (MOL) Bulb Diameter (DIA) 4.750 in(120.6 mm) Bulb Diameter (DIA) (MAX) 4.750 in(120.6 mm)

### **PRODUCT INFORMATION**

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168104739