

# *Rough Service™ and Bonus Life™* Incandescent Lamps



**R20**



**ER30**



**BR30**



**BR40**



**PAR38**

| LAMP         | WATTS | BASE | VOLTS | DESCRIPTION      | BEAM SPREAD | ORDERING CODE | QTY/ CASE | AVERAGE RATED LIFE | LUMENS | C.B.C.P.* | M.O.L.** |
|--------------|-------|------|-------|------------------|-------------|---------------|-----------|--------------------|--------|-----------|----------|
| <b>R20</b>   | 28/30 | MED  | 120   | 28/30 R20 HF     | FLOOD       | L-789         | 60        | 5,000              | 205    | 75        | 3.77"    |
|              | 28/30 | MED  | 120   | • 28/30 R20 HF   | FLOOD       | L-795         | 60        | 9,000              | 205    | 50        | 3.77"    |
|              | 30    | MED  | 120   | • 30 R20 LF      | SPOT        | L-114         | 60        | 20,000             | 195    | 150       | 3.77"    |
|              | 50    | MED  | 120   | • 50 R20 LF      | SPOT        | L-121         | 60        | 20,000             | 400    | 300       | 3.77"    |
| <b>ER30</b>  | 50 \$ | MED  | 120   | 50 ER30 LF       | SPOT        | L-124         | 30        | 20,000             | 450    | 600       | 6.10"    |
|              | 75 \$ | MED  | 120   | 75 ER30 LF       | SPOT        | L-134         | 30        | 20,000             | 750    | 800       | 6.10"    |
| <b>BR30</b>  | 45/50 | MED  | 120   | • 45/50 BR 30 LF | SPOT        | L-801         | 30        | 9,000              | 320    | 250       | 5.39"    |
|              | 45/50 | MED  | 120   | • 45/50 BR 30 HF | FLOOD       | L-779         | 30        | 9,000              | 320    | 150       | 5.39"    |
|              | 65    | MED  | 120   | • 65 BR 30 HF    | FLOOD       | L-809         | 30        | 20,000             | 420    | 200       | 5.39"    |
|              | 75    | MED  | 120   | • 75 BR 30 HF    | FLOOD       | L-132E        | 30        | 20,000             | 750    | 250       | 5.39"    |
| <b>BR40</b>  | 100   | MED  | 120   | 100 BR40 HF      | FLOOD       | L-148         | 24        | 20,000             | 1,150  | 800       | 6.37"    |
|              | 150   | MED  | 120   | 150 BR40 HF      | FLOOD       | L-167E        | 24        | 20,000             | 1,500  | 1,000     | 6.37"    |
| <b>PAR38</b> | 54    | MED  | 120   | • 54 PAR38 FL    | FLOOD       | L-914         | 24        | 9,000              | 850    | 600       | 5.31"    |
|              | 75    | MED  | 120   | • 75 PAR38 FL    | FLOOD       | L-135         | 24        | 20,000             | 750    | 1,600     | 5.70"    |
|              | 100   | MED  | 120   | • 100 PAR38 FL   | FLOOD       | L-153         | 24        | 20,000             | 1,100  | 2,000     | 5.70"    |
|              | 150   | MED  | 120   | • 150 PAR38 FL   | FLOOD       | L-173A        | 24        | 20,000             | 1,450  | 2,300     | 5.70"    |

\$ Energy Savings, 50 and 75-watt ER lamps replace 75 and 100-watt reflector lamps, respectively, while providing the same usable light.

\* Center Beam Candle Power

\*\* Maximum Overall Length (in inches)