

S9396

100W/LED/HID/5000K/100-277V/EX39 100 watt - LED HID Replacement (up to 400W); 5000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixturesDamp location IP65 rated
- For outdoor & indoor use
- DLC Qualified
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C
- · Safety chain included

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in surge protection

Minimum lamp compartment dimensions:

235mm x 235mm x 440mm (9.25" x 9.25" x 17.3")

Optional accessory: In-line surge protector 80-929



S9396

Item Number	Product Line	UPC	Input Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S9396	Hi-Pro	045923093968	100 - 277	100	500W	150W	400W

Base	ANSI	Lown Code	Dimmable/Non-	Finish	MOL In	MOD In	Initial
	Base	Lamp Code	Dimmable	Finish	Inches	Inches	Lumens

Extended		277V/E	X39							
Average Rated Hours	Kelvin Temp	Color	CRI	Beam S	Spread eg	Operating Temperature		Pack	Package Type	
50000	5000	Natural Ligh	t 80+	30	00	-20C (-4F) to a maximum of +65C (+149F)		4	Box	
DLC ID:			RoHS Compliant			r ETL UL Classification				Warranty
Search under: S9396A or P93FAQCD or PE62TJJC DLC Search			Yes	S	Y	es	cULus - Dan	np Location	Rated	5 Year Limited

Non-Dimmable



EX39

National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

100W/LED/HID/5000K/100-

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027

White

9-5/8"



13300

@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051