

S39396

100W/LED/HID/5000K/100-277V/EX39 100 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
- Damp location IP64 rated
- For outdoor & indoor use
- Base up or base down operation
- High-bay / Low-bay / Post-topEmits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cÚLus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 6KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size								
Length	Width	Depth						
9.25 inch	9.25 inch	17.32 inch						

Optional Accessories

• In-line surge protector 80-929



S39396

S39	9396	Hi-Pro	04592330	3968	38 100 - 277 10		100	50/60H	0/60Hz 500\		<i>N</i> 150W		
	IID ivalent	Base	ANSI Base		Lamp Code		[Dimmable/Non- Dimmable	Finish	MOL In Inches	MOD In Inches		
40	WOC	Mogul Extended	EX39	100	100W/LED/HID/5000K/100- 277V/EX39			Non-Dimmable	White	9"	4-23/32"		
		Average Rate Hours	d Kelv Ten		Color CRI Beam Spre		ead	Burning Position		Operating Temperature			
14300		50000	500	00	Natural 80 30		300		Up or Down Operation Only		-20C (-4F) to a maximum of +65C (+149F)		
Pack	Packag Type	CEC SIAII	CEC Status DLC ID: Material		ial	RoHS Compliant	UL o ETL Liste	UL Classification	on Warı	Warranty Thermal Managemen			
12	Box	Lawful fo sale in California	LPJL3	0QF2F2 earch	Alumin	ium	Yes	Yes	cULus - Damp Location Rate		ear <u>Mo</u> ited	re Details About	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051