

S39676

100W/LED/HID/4000K/100-277V/EX39 100 watt - LED HID Replacement; 4000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
- Damp location IP64 rated
- For outdoor & indoor useBase up or base down operation
- High-bay / Low-bay / Post-topEmits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cÚLus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 6KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size								
Length	Width	Depth						
9.25 inch	9.25 inch	17.32 inch						

Optional Accessories

• In-line surge protector 80-929



S39676

S39	0676	Hi-Pro	045923306	6761 1	100 - 277 10		50/	60Hz 500		W	150W		
	IID ivalent	Base	ANSI Base		Lamp Code				mable/Non- Dimmable	Finish	MOL In Inches	MOD In Inches	
40	W00	Mogul Extended	EX39	100W	100W/LED/HID/4000K/100- 277V/EX39			Non	n-Dimmable	White	9"	4-23/32"	
	itial mens	Average Rate Hours		Gelvin Color CRI Beam Sprea Femp Deg			Bur	Burning Position		Operating Temperature			
14000		50000	400	()	Cool White 80		300		Up or Down Operation Only		-20C (-4F) to a maximum of +65C (+149F)		
Pack	Packag Type	CEC SIAIU	ıs DL	C ID:	Material	Rol- Comp	dS diant	JL or ETL Listed	UL Classificatio	n Warr	antv	Thermal Inagement	
12	Box	Lawful for sale in California	DLC Se		Aluminun	n Ye	es	Yes	cULus - Damp Location Rated			ore Details About	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051