

Presented By: Candela Corporation
 Contact Phone: 800-922-9226
 Contact E-mail: sales@candelacorp.com



Customer Name:
 Project Name:
 Fixture Type:



GE
 Lighting

26838 - 1073

GE S8 - Automotive; Low Voltage



GENERAL CHARACTERISTICS

Lamp Type	Miniature - S Shape
Bulb	S8
Base	Single Contact Bayonet (BA15s)
Filament	C-6
Rated Life (NOM)	200.0 h
Atmosphere	Gas-filled
Primary Application	Low Voltage;Back up;High Mount Stop;Parking;Stop;Tail;Turn Signal, Front;Turn Signal, Rear

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	402.0
Nominal Initial Lumens per Watt (NOM)	17.47826
Mean Spherical Candlepower (MSCP) (NOM)	32.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	23.0
Voltage (NOM)	12.8

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	2.000 in(50.8 mm)
Bulb Diameter (DIA) (NOM)	1.000 in(25.4 mm)
Light Center Length (LCL) (NOM)	1.250 in(31.8 mm)

PRODUCT INFORMATION

Product Code	26838
Description	1073
ANSI Code	1073
Standard Package	Case
Standard Package GTIN	20043168268381
Standard Package Quantity	50
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	50
UPC	043168268387