



# S9997

11.5T8U6/LED/22.5-850/DR  
 11.5 watt T8 U-Bend LED; 50000 average rated hours; Medium bi-pin base; 1800 lumens; 5000K



### Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required\*
- Solid State LED lighting
- High efficacy
- Long life

\*May not be compatible with all electronic ballasts.  
 Ballast required

S9997

View:

[Ballast Compatibility Chart](#)

Item Number	UPC	Watts	Lamp Shape	Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable
S9997	045923099977	11.5	T8	Medium Bi-Pin	G13	11.5T8U6/LED/22.5-850/DR	Non-Dimmable

Finish	MOL In Inches	MOD In Inches	Leg Spacing	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
White	22.5"	7.00"	6"	1800	50000	5000	Natural Light

CRI	Beam Spread Deg	Pack	Package Type	CEC Status	DLC ID:	RoHS Compliant	UL or ETL Listed
82	230	12	Box	Lawful for sale in California	PYPGJB67 <a href="#">DLC Search</a>	Yes	Yes

UL Classification							
cULus - Damp Location Rated							



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

