

LINE NO.	LAMP NUMBER	PRIMARY APPLICATION	DESIGN VOLTS	DESIGN WATTS	DESIGN AMPS	APPROX. CANDLE-POWER	RATED AVERAGE LAB LIFE HOURS	BASE TYPE	MAXIMUM OVERALL LENGTH (inches)	LIGHT CENTER LENGTH (inches)	FILAMENT TYPE	FIG. NO.
S-8 Bulb 1" (25mm) Diameter (Continued)												
1	87	Automotive	6.75	12.89	1.91	15.00	300	S.C. Bayonet	2.000	1.125	C-2R	20
2	88	Indicator	6.75	12.89	1.91	15.00	300	D.C. Bayonet	2.000	1.125	C-6	25
3	17881	Signal, Stop, Automotive	12.00 12.00	21.00 4.00	1.75 0.33	35.00 1.20	150 1500	BAZ15d	2.095	1.250	C-6 C-6	85
4	17916	Signal, Stop, Automotive	12.00 12.00	21.00 5.00	1.75 0.42	35.00 1.20	150 1500	BAY15d	2.095	1.250	C-6 C-6	86
5	17635	Signal, Stop, Automotive	12.00	21.00	1.75	37.00	150	BA15s	2.095	1.250	C-6	84
6	17638NA	Signal, Automotive, Natural Amber	12.00	21.00	1.75	37.00	300	BAU15s	2.095	1.250	C-6	110
7	1295NA	Signal, Automotive	12.50	37.50	3.00	37.00	200	S.C. Bayonet	2.000	1.250	C-2R	20
8	1295	Automotive	12.50	37.50	3.00	50.00	300	S.C. Bayonet	2.000	1.250	C-2R	20
9	93	Automotive	12.80	13.31	1.04	15.00	500	S.C. Bayonet	2.000	1.125	C-2R	20
10	94	Automotive, Marine	12.80	13.31	1.04	15.00	500	D.C. Bayonet	2.000	1.125	C-6	25
11	1093*	Automotive	12.80	15.23	1.19	15.00	1,000	S.C. Bayonet	2.000	1.125	C-2R	20
12	1034A*	Park, Signal, Automotive, Translucent Outside Amber Coating	12.80 14.00	23.04 8.26	1.80 0.59	18.00 1.70	200 5,000	D.C. Index	2.000	1.250	C-6 C-6	21
13	1157A*	Park, Signal, Automotive, Translucent Outside Amber Coating	12.80 14.00	26.88 8.26	2.10 0.59	18.00 1.70	1,200 5,000	D.C. Index	2.000	1.250	C-6 C-6	21
14	1005*	Automotive	12.80 12.80	16.77 16.77	1.31 1.31	21.00 21.00	300 300	D.C. Bayonet	2.000	1.250	C-2R C-2R	25
15	1016	Automotive	12.80 14.00	17.15 8.26	1.34 0.59	21.00 6.00	200 1,000	D.C. Index	2.000	1.250	C-6 C-6	21
16	1034NA*	Park, Signal, Automotive, Natural Amber	12.80 14.00	23.04 8.26	1.80 0.59	21.00 2.20	200 5,000	D.C. Index	2.000	1.250	C-6 C-6	21
17	1141	Automotive	12.80	18.43	1.44	21.00	500	S.C. Bayonet	2.000	1.250	C-6	20
18	1141LL	Automotive, Krypton	12.80	18.43	1.44	21.00	1,000	S.C. Bayonet	2.000	1.250	C-6	20
19	1142	Automotive	12.80	18.43	1.44	21.00	500	D.C. Bayonet	2.000	1.250	C-6	25
20	1159	Automotive, Fleet Duty	12.80	20.48	1.60	21.00	1,500	S.C. Bayonet	2.000	1.250	C-6	20
21	1176	Automotive	12.80 14.00	17.15 8.26	1.34 0.59	21.00 6.00	200 1,000	D.C. Bayonet	2.000	1.250	C-2R C-2R	25
22	1168*	Automotive	12.80	18.30	1.43	21.00	500	D.C. Prefocus	2.000	1.125	C-6	22
23	1156NA	Signal, Automotive, Natural Amber	12.80	26.88	2.10	24.00	1,200	S.C. Bayonet	2.000	1.250	C-6	20
24	1157NA	Park, Signal, Automotive, Natural Amber	12.80 14.00	26.88 8.26	2.10 0.59	24.00 2.20	1,200 5,000	D.C. Index	2.000	1.250	C-6 C-6	21
25	1157NALL	Park, Signal, Automotive, Krypton	12.80 14.00	26.88 8.26	2.10 0.59	24.00 2.20	2,000 10,000	D.C. Index	2.000	1.250	C-6 C-6	21

NOTE: CIM = Construction Industrial Machinery D.C. = Double Contact MP = Multipurpose Rt. = Right S.C. = Single Contact
***This part number is included for reference only and inventory may not be available.**