



S11929

12.5T8/LED/48/840-850-865/BP

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	12.5W
Color Temperature:	4000K/5000K/6500K
Length:	48.00"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	12.5W
Volts:	120V-277V
Fluorescent Equivalent:	32W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	White
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	4000K/5000K/6500K
CRI:	83CRI
Lumen Output:	1800L

Dimmable:	Non-Dimmable
Beam Spread:	220D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	Ballast Bypass
Ballast Type:	Type B
Single / Dual End:	Single Ended, Double Ended
Tube Guard Use:	Not Approved
Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Technology:	LED
Material:	Plastic

DIMENSIONS

MOL:	48.00"
MOD:	1.00"
Weight:	0.35

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	P113ABSC
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	US/CN - E356817; US/CN - E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923119293	Case UPC:	10045923119290
Each Quantity:	25	Case Quantity:	25
Each Dimensions:	30.00 x 6.50 x 6.70	Case Dimensions:	50.00 x 6.50 x 6.70
1 on Centers		Copyright 2022	
Brentwood, NY 11717	New York, Florida,	National Toll-Free	Satco Products, Inc.
PH 631-243-2022	Texas, Washington,	800-43-SATCO	All Rights Reserved
FX 631-243-2027	California, Puerto Rico	(800-437-2826)	July 15, 2022
		www.satco.com	