



S28717

120W/LED/HID/5000K/277-347V/EX39
 120 watt - LED HID Replacement; 5000K; Mogul extended base; 277-347 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 277 - 347V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C
- Safety chain included

Additional Technical Specifications

- Operating Frequency 50-60Hz
- Working Voltage AC 250-380V
- Power Factor >0.9

Minimum Compartment Size		
Length	Width	Depth
17.3 inch	9.25 inch	9.25 inch

Optional accessory: In-line surge protector [80-935](#)



S28717

Item Number	Product Line	UPC	Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S28717	Hi-Pro	045923287176	277-347	120	750W	200W	600W

Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Mogul Extended	EX39	120W/LED/HID/5000K/277-347V/EX39	Non-Dimmable	White	10-3/8"	5-7/8"	16000

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type
---------------------	-------------	-------	-----	-----------------	-----------------------	------	--------------

50000	5000	Natural Light	80+	300	-20C (-4F) to a maximum of +65C (+149F)	4	Box
DLC ID:		RoHS Compliant	UL Classification		Warranty	Thermal Management	
PLOGLD9J32WB; PL2RICVYUIE8 DLC Search		Yes	cULus - Wet Location Rated		5 Year Limited	More Details About	