

LED GLOBE LAMP
G40 SERIES



PRODUCT DESCRIPTION:

MaxLite's LED G40 Globe is ideal for providing clear general lighting for globe, vanity and decorative fixtures throughout homes and hospitality applications. It consumes only 12 watts and replaces a 100-watt incandescent bulb, resulting in up to 88% savings in energy.

FEATURES:

- Wattage: 12W, replaces 100W Inc.
- Lumens: 950
- CRI: 83
- Color Temperature: 3000K
- Base: E26 base
- Volts: 120V
- Frequency: 60Hz
- Instant on
- Dimmable down to 10%
- ENERGY STAR Certified
- Operating temperature range: -4° - 104°F
- Not suitable for use in enclosed luminaire
- Suitable for damp locations
- 3 year warranty
- 15,000 hour life at L70 standards

APPLICATIONS:

- Vanity Fixture
- Pendant fixture
- Bath bar fixture
- Wall fixture

MODEL SELECTION (Full list of order codes on pg. 2)			Typical order example: 12G40DLED30		
12G40		DLED		30	
FAMILY		DIMMABILITY		COLOR TEMPERATURE (CCT)	
12G40= 12 Watt, LED Globe 40		DLED= Dimmable		30= 3000K	

COMPATIBLE DIMMERS:

MANUFACTURE	DIMMER MODEL
LEVITON	6681
	IPL06
	IPI06
	RTD01-10Z
	6161
	IPE04
	6633-P
	6674

MANUFACTURE	DIMMER MODEL
LUTRON	S-600P
	LGCL-153P
	LGCL-153PL
	MAELV-600
	DVCL-153P
	CTCL-153P
	VELV-600M
	CTELV-303P
	DVELV-303P

MANUFACTURE	DIMMER MODEL
LUTRON	VELV-600M
	RRD-6NA
	DVCL-153P
	NTLV-600
	S-603P
	DV-603P
	SELV-300P
	SLV-600P
	IPX10-1

SPECIFICATIONS:

		12G40DLED30
ITEM	SPECIFICATION	DETAILS
GENERAL PERFORMANCE	Watt (W)	12
	Lumens Delivered (lm)	950
	Efficacy (lm/W)	79
	Equivalency	100W Inc.
	CRI	83
	Color Temperature	3000K
	Lumen Maintenance (L70)	15,000 hours
ELECTRICAL	Power Factor	≥0.90
	Input Voltage	120V
PHYSICAL	Operating Temperature	-4°F to 104°F
APPLICATION	Environment	Dry, Damp
	Certification	Energy Star, ETL Listed
	Warranty	3 Year

ORDERING:

ORDER CODE	MODEL	ENERGY STAR	WATTAGE	DELIVERED LUMENS	INCANDESCENT EQUIVALENCY	CRI	CCT (K)	DIMENSION (MOL" X W")
1410218	12G40DLED30	★	12	950	40W Inc.	83	3000K	6.38" x 4.72"

★ ENERGY STAR Certified