

A smooth design solution for a seamless look.



PHILIPS LED SINGLE OPTIC PAR30S LAMPS WITH AIRFLUX TECHNOLOGY



Philips LED Single Optic PAR30S Lamps with AirFlux Technology provide superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

High efficacy LED reflector lamp

- Single Optic reduces glare to improve shopper experience
- 25,000-hour rated average life for Energy Star® Qualified lamps*
- 50,000-hour design life**
- 12W PAR30S saves 63 watts when compared to a 75W halogen PAR30S
- 83 CRI for excellent color rendering
- Virtually UV/IR free in the beam
- Contains no mercury
- Select lamps available in black finish

Easy to experience

- Will not fade colors, avoids inventory spoilage
- Lowers maintenance costs by reducing re-lamp frequency
- 5-year limited warranty‡

(*, **, ‡ See back page for footnotes)



PHILIPS

PHILIPS LED SINGLE OPTIC PAR30S LAMPS WITH AIRFLUX TECHNOLOGY

Ordering, Electrical and Technical Data (Subject to change without notice)

| Product Number | Model Number | Ordering Code | Nom. Watts | Description | Energy Star Qualified Life (hrs) ¹ | Rated Average Life (Yrs) ² | Approx. Lumens | MBCP ³ | Est. Energy Cost ⁴ | Color Temp. (K) |
|----------------|--------------|--------------------------------|------------|----------------------------|---|---------------------------------------|----------------|-------------------|-------------------------------|-----------------|
| 43236-9 | 9290002621 | I2PAR30S/S15 2700 ND AF RO 6/I | 12 | PAR30S I2W 15° 2700K | 25000 | 22.7 | 850 | 7400 | \$1.45 | 2700 |
| 43237-7 | 9290002622 | I2PAR30S/S15 3000 ND AF RO 6/I | 12 | PAR30S I2W 15° 3000K | 25000 | 22.7 | 850 | 7900 | \$1.45 | 3000 |
| 43238-5 | 9290002623 | I2PAR30S/S15 4000 ND AF RO 6/I | 12 | PAR30S I2W 15° 4000K | 25000 | 22.7 | 900 | 8500 | \$1.45 | 4000 |
| 42692-4 | 9290002354 | I2PAR30S/F25 2700 AF SO | 12 | PAR30S I2W 25° 2700K | 25,000 | 22.7 | 850 | 5000 | \$1.45 | 2700 |
| 43296-2 | 9290002654 | I2PAR30S/F25 2700 AF SO-B | 12 | PAR30S I2W 25° 2700K Black | 25,000 | 22.7 | 850 | 5000 | \$1.45 | 2700 |
| 42693-2 | 9290002355 | I2PAR30S/F25 3000 AF SO | 12 | PAR30S I2W 25° 3000K | 25,000 | 22.7 | 900 | 5300 | \$1.45 | 3000 |
| 43297-0 | 9290002655 | I2PAR30S/F25 3000 AF SO-B | 12 | PAR30S I2W 25° 3000K Black | 25,000 | 22.7 | 900 | 5300 | \$1.45 | 3000 |
| 42694-0 | 9290002356 | I2PAR30S/F25 4000 AF SO | 12 | PAR30S I2W 25° 4000K | 25,000 | 22.7 | 950 | 5500 | \$1.45 | 4000 |
| 42695-6 | 9290002357 | I2PAR30S/F36 2700 AF SO | 12 | PAR30S I2W 36° 2700K | 25,000 | 22.7 | 850 | 1850 | \$1.45 | 2700 |
| 42696-4 | 9290002358 | I2PAR30S/F36 3000 AF SO | 12 | PAR30S I2W 36° 3000K | 25,000 | 22.7 | 900 | 1960 | \$1.45 | 3000 |
| 42697-2 | 9290002359 | I2PAR30S/F36 4000 AF SO | 12 | PAR30S I2W 36° 4000K | 25,000 | 22.7 | 950 | 2100 | \$1.45 | 4000 |

1. Early initial qualification for Energy Star allows for directional lamp life claims of 25,000 hours (L70) with 3,000 hour actual test data, LM80 data and in-situ temperature measurements. As the lamps pass Energy Star requirements, manufacturers may increase the lifetime of a product as dictated by Energy Star guidelines. See http://www.energystar.gov/index.cfm?fuseaction=products_for_partners.showLightbulbs for further details.
 2. Based on average usage of 3 hrs/day, 7 days/week.
 3. Based on photometric testing consistent with IES LM-79. Maximum Beam Candlepower.
 4. Based on 3 hrs/day, 1 l/g/kVWh. Cost depends on rates and use.
 5. Light output comparison based upon the ENERGY STAR® Integral LED Lamp Center Beam Intensity Benchmark tool which can be found at EnergyStar.gov/LEDbulbs, LED Light Bulbs for Partners, Program Requirements PDF Pg. 11.
- This lamp is ENERGY STAR® Certified.

Footnotes from front:

- * Early initial qualification for Energy Star allows for directional lamp life claims of 25,000 hours (L70) with 3,000 hour actual test data, LM80 data and in-situ temperature measurements. As the lamps pass Energy Star requirements, manufacturers may increase the lifetime of a product as dictated by Energy Star guidelines. See http://www.energystar.gov/index.cfm?fuseaction=products_for_partners.showLightbulbs for further details.
- ** Design life is based on engineering testing and probability analysis
- ‡ For details, please visit http://www.usa.lighting.philips.com/connect/tools_literature/warranties.wpd

Shipping Data (Subject to change without notice)

| Product Number | SKU UPC (0-46677) | Outer Bar Code (5-00-46677) | Case Qty. | Case Weight (lbs.) | Case Cube (cu. ft.) | Pallet Qty. | SKUs per Layer | Layers High | SKU Dimensions (W x D x H) (In.) | Case Dimensions (W x D x H) (In.) | Pallet Dimensions (W x D x H) (In.) |
|----------------|-------------------|-----------------------------|-----------|--------------------|---------------------|-------------|----------------|-------------|----------------------------------|-----------------------------------|-------------------------------------|
| 43236-9 | 43236-2 | 43236-7 | 6 | 5.59 | 0.328 | 672 | 96 | 7 | 4.0 x 4.0 x 4.9 | 12.6 x 8.4 x 5.3 | 47.2 x 39.4 x 43.1 |
| 43237-7 | 43237-9 | 43237-4 | 6 | 5.59 | 0.328 | 672 | 96 | 7 | 4.0 x 4.0 x 4.9 | 12.6 x 8.4 x 5.3 | 47.2 x 39.4 x 43.1 |
| 43238-5 | 43238-6 | 43238-1 | 6 | 5.59 | 0.328 | 672 | 96 | 7 | 4.0 x 4.0 x 4.9 | 12.6 x 8.4 x 5.3 | 47.2 x 39.4 x 43.1 |
| 42692-4 | 42692-7 | 42692-2 | 6 | 5.59 | 0.328 | 672 | 96 | 7 | 4.0 x 4.0 x 4.9 | 12.6 x 8.4 x 5.3 | 47.2 x 39.4 x 43.1 |
| 43296-2 | 43296-6 | 43296-1 | 6 | 5.59 | 0.328 | 672 | 96 | 7 | 4.0 x 4.0 x 4.9 | 12.6 x 8.4 x 5.3 | 47.2 x 39.4 x 43.1 |
| 42693-2 | 42693-4 | 42693-9 | 6 | 5.59 | 0.328 | 672 | 96 | 7 | 4.0 x 4.0 x 4.9 | 12.6 x 8.4 x 5.3 | 47.2 x 39.4 x 43.1 |
| 43297-0 | 43297-3 | 43297-8 | 6 | 5.59 | 0.328 | 672 | 96 | 7 | 4.0 x 4.0 x 4.9 | 12.6 x 8.4 x 5.3 | 47.2 x 39.4 x 43.1 |
| 42694-0 | 42694-1 | 42694-6 | 6 | 5.59 | 0.328 | 672 | 96 | 7 | 4.0 x 4.0 x 4.9 | 12.6 x 8.4 x 5.3 | 47.2 x 39.4 x 43.1 |
| 42695-6 | 42695-8 | 42695-3 | 6 | 5.59 | 0.328 | 672 | 96 | 7 | 4.0 x 4.0 x 4.9 | 12.6 x 8.4 x 5.3 | 47.2 x 39.4 x 43.1 |
| 42696-4 | 42696-5 | 42696-0 | 6 | 5.59 | 0.328 | 672 | 96 | 7 | 4.0 x 4.0 x 4.9 | 12.6 x 8.4 x 5.3 | 47.2 x 39.4 x 43.1 |
| 42697-2 | 42697-2 | 42697-7 | 6 | 5.59 | 0.328 | 672 | 96 | 7 | 4.0 x 4.0 x 4.9 | 12.6 x 8.4 x 5.3 | 47.2 x 39.4 x 43.1 |

WARNINGS AND CAUTIONS

- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.
- Before replacing, turn off power and let lamp cool to avoid electrical shock or burn.

CAUTION: Risk of electric shock—do not use where directly exposed to water

NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005

