



**S11652R1** - 15 Watt T5 LED; 35K/4K/5K/65K CCT Selectable; 48 Inch; G5 Base; Type B; PET Coated; Line Voltage Dimmable; 120-347 Volt


**GENERAL**

Company	SATCO
EA Height	0.75
EA Width	0.75
EA Length	45.67
Lamp Ballast Type AB	Type B
Material	Plastic
Fixture Type	Linear
Status	Active
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	<20%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.130-0.040A
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	48.0
Operating Position	Universal
Power Factor	>0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	28W
Incandescent Equivalent	100W

**ELECTRICAL**

CCT (Kelvin Temp)	3500K/4000K/5000K/6500K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	180
Color Temp	Neutral White to Daylight
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1900L
Volts	120V-347V
Watts	15W

**PHYSICAL**

Lamp Base	Miniature Bi Pin
Finish	Frost
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.62
MOL	45.75

**ADDITIONAL INFO**

Warranty	5-Years
Rated For Enclosed Fixture	Yes

**PACKAGING**

UPC	045923409974
Case Cube	0.5704
Case Height	4.72
Case Length	48.23
Case Quantity	25
Case UPC	10045923409971
Case Weight	8.9
Case Width	4.33
EA Cube	0.0149
EA Height	0.75
EA Length	45.67
EA Quantity	1
EA Weight	0.33
EA Width	0.75
Pack Type	Sleeve
Web Length	45.75
Web Width	0.62

**COMPLIANCE**

Dark Sky Rated	No
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Classified
California Ban	Lawful for sale
Title 20	Exempt
T24 Compliant	No