



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S18413 - 11.5/13/15 Wattage Selectable T8 U-Bend LED;
 30K/35K/40K/50K/65K CCT Selectable; 6-Inch; Frost Finish;
 120-277 Range Voltage

- Wattage Selectable
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	11.5W/13W/15W
Volts:	120V-277V
Lumens:	1800L/2000L/2200L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	210
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Incandescent Equivalent :	50W
Fluorescent Equivalent :	32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Ballast Type A/B/C :	Type A/B
Lamp End Type :	Single Ended; Double Ended
THD:	<20%
Power Factor :	>0.9
Light Source:	LED
Warranty:	5 Year Limited - T8 LED Bulbs

PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Frost
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 0.96 - MOD: 0.96
Weight (Lbs.):	0.55
Material:	Glass
Leg Spacing:	5.98

COMPLIANCE

Safety Listing:	cULus - Listed; cULus - Classified
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Rated For Enclosed Fixture:	No
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

PACKAGING

Each UPC:	045923184130
Each Quantity:	1
Each Dimensions:	23.03 x 1.22 x 1.22

INFO

Installation Note:	Not for use in vapor tight fixtures.
--------------------	--------------------------------------