



# A-Shape LED

## 16.6A19/LED/950/FR/P/E26/ND/T20 6/1FB

Philips A-shape LED lamps are the LED alternative to standard incandescents. It provides beautiful light and dependable performance you expect from LED at an affordable price.

### Product data


General Information	
Lighting Technology	LED
Switching Cycle	50,000
Nominal lifetime	11,000 hour(s)
Cap-Base	E26 [Single Contact Medium Screw]
Light Technical	
Color Code	950 [CCT of 5000K]
Beam Angle (Nom)	250 degree(s)
Luminous Flux	1,500 lumen
Color Designation	Daylight
Correlated Color Temperature (Nom)	5000 K
Luminous Efficacy (rated) (Nom)	90.00 lm/W
Color Consistency	<4
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	60 Hz
Input Frequency	60 Hz
Power Consumption	16.6 W
Lamp Current (Nom)	118 mA
Wattage Equivalent	100 W
Starting Time (Nom)	0.5 s

Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.7
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	194 °F
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Plastic
Bulb Shape	A19 [A 19mm]
Approval and Application	
Energy Certifications	No
EU RoHS compliant	Yes
Product Data	
Order product name	16.6A19/LED/950/FR/P/E26/ND/T20 6/1FB
Order code	571695
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6

A-Shape LED



Material number (12NC)	929003021004
Full product name	16.6A19/LED/950/FR/P/E26/ND/T20 6/1FB
EAN/UPC - Case	50046677571691

Dimensional drawing




Product	D	C
16.6A19/LED/950/FR/P/E26/ND/T20 6/1FB	60 mm	117 mm

Photometric data



General uniform lighting - 16.6A19/LED/950/FR/P/E26/ND/T20 6/1FB

Spectral Power Distribution Colour - 16.6A19/LED/950/FR/P/E26/ND/T20 6/1FB




Light Distribution Diagram - 16.6A19/LED/950/FR/P/E26/ND/T20 6/1FB

A-Shape LED

Lifetime



Lumen Maintenance Diagram - 16.6A19/LED/950/FR/P/E26/ND/T20 6/1FB



Life Expectancy Diagram - 16.6A19/LED/950/FR/P/E26/ND/T20 6/1FB

