

## BUTTERFLY

Ø 26mm. - G13 cap

Watts	Bulb	Base	Product Code	Order Code	Pkg	CRI	Lumens	Life (HRS)	Kelvin	MOL
<b>2700K</b>										
10	GR8	2-Pin	1D10102P	GR8/2-Pin/10W	20	85	600	10,000	2700	3 3/4
10	GR10q	4-Pin	1D10104P	GR10q/4-Pin/10W	20	85	600	10,000	2700	3 3/4
16	GR8	2-Pin	1D10162P	GR8/2-Pin/16W	20	85	1000	10,000	2700	5 5/8
16	GR10q	4-Pin	1D10164P	GR10q/4-Pin/16W	20	85	1000	10,000	2700	5 5/8
21	GR8	2-Pin	1D10212P	GR8/2-Pin/21W	20	85	1300	10,000	2700	5 5/8
21	GR10q	4-Pin	1D10224P	GR10q/4-Pin/21W	20	85	1300	10,000	2700	5 5/8
28	GR8	2-Pin	1D10282P	GR8/2-Pin/28W	20	85	2000	10,000	2700	8 1/8
28	GR10q	2-Pin	1D10284P	GR10q/4-Pin/28W	20	85	2000	10,000	2700	8 1/8
38	GR10q	4-Pin	1D10384P	GR10q/4-Pin/38W	20	85	2800	10,000	2700	8 1/8
<b>3500K</b>										
16	GR8	2-Pin	1D10152P	GR8/2-Pin/16W	20	85	1000	10,000	3500	3 3/4
16	GR10q	4-Pin	1D10154P	GR10q/4-Pin/16W	20	85	1000	10,000	3500	3 3/4
21	GR8	2-Pin	1D10202P	GR8/2-Pin/21W	20	85	1300	10,000	3500	5 5/8
21	GR10q	4-Pin	1D10204P	GR10q/4-Pin/21W	20	85	1300	10,000	3500	5 5/8
28	GR8	2-Pin	1D10272P	GR8/2-Pin/28W	20	85	2000	10,000	3500	8 1/8
28	GR10q	4-Pin	1D10274P	GR10q/4-Pin/28W	20	85	2000	10,000	3500	8 1/8
38	GR10q	4-Pin	1D10374P	GR10q/4-Pin/38W	20	85	2800	10,000	3500	8 1/8
<b>4000K</b>										
10	GR8	2-Pin	1D10112P	GR8/2-Pin/10W	20	85	600	10,000	4000	3 3/4
10	GR10q	4-Pin	1D10114P	GR10q/4-Pin/10W	20	85	600	10,000	4000	3 3/4
16	GR8	2-Pin	1D10172P	GR8/2-Pin/16W	20	85	1000	10,000	4000	5 5/8
16	GR10q	4-Pin	1D10184P	GR10q/4-Pin/16W	20	85	1000	10,000	4000	5 5/8
21	GR8	2-Pin	1D10232P	GR8/2-Pin/21W	20	85	1300	10,000	4000	5 5/8
21	GR10q	4-Pin	1D10244P	GR10q/4-Pin/21W	20	85	1300	10,000	4000	5 5/8
28	GR10q	4-Pin	1D10294P	GR10q/4-Pin/28W	20	85	2000	10,000	4000	8 1/8
38	GR10q	4-Pin	1D10394P	GR10q/4-Pin/38W	20	85	2800	10,000	4000	8 1/8
<b>6400K</b>										
16	GR8	2-Pin	1D10132P	GR8/2-Pin/16W	20	85	1000	10,000	6400	5 5/8
16	GR10q	4-Pin	1D10134P	GR10q/4-Pin/16W	20	85	1000	10,000	6400	5 5/8
21	GR8	2-Pin	1D10142P	GR8/2-Pin/21W	20	85	1300	10,000	6400	5 5/8
21	GR10q	4-Pin	1D10144P	GR10q/4-Pin/21W	20	85	1300	10,000	6400	5 5/8



- Life 10.000 h
- Up to 80% power saving.

CERTIFIED COMPANY



ISO 9002