

2-0345 2-0346 2-0347

Square Puff Ceiling Fixture



Features

Housing

Die-formed Cold-rolled Steel

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Electrical

High Power Factor, Low THD

Lamp

LED Type: Built-in (More Color Temperature Option – 3500K, 4000K, 5000K)


CFL Type: GU24 CFL Lamp (Color Temperature Option – 2700K, 4000K)

Certifications

UL/cUL or ETL/cETL Listed, Suitable for Damp Locations

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (Typ)	Dimension (L X W X H)	Energy Star
2-0345D-xxxxK	120V	17W	3000K	> 80	1590	11.0" x 11.0" x 3.2"	Yes
2-0346D-xxxxK	120V ~ 277V	24W	3000K	> 80	2384	14.0" x 14.0" x 3.4"	Yes
2-0347D-xxxxK	120V ~ 277V	35W	3000K	> 80	3250	19.0" x 19.0" x 3.4"	Yes

CFL Type

Model	Input Voltage	Input Wattage	Shade	Lamp	Dimension (L X W X H)	Energy Star
2-0345PG-123	120V	23W	Opal Acrylic	1 x 23W GU24	11.0" x 11.0" x 3.2"	
2-0346PG-213	120V	26W	Opal Acrylic	2 x 13W GU24	14.0" x 14.0" x 3.4"	
2-0347PG-318	120V	54W	Opal Acrylic	3 x 18W GU24	19.0" x 19.0" x 3.4"	