



Product Number: 58302

Order Abbreviation: 20MR16/TWFL60/C 12V

General Description: Tungsten Halogen Tru-Aim MR16 TITAN Axial Filament UV-Filter Hard Dichroic Reflector Cover Glass GU5.3 Bi-Pin Base 20Watt 12Volt WFL Beam

Product Information	
Abbrev. With Packaging Info.	20MR16TWFL60C 12V 20/CS 1/SKU
Average Rated Life (hr)	4000
Base	GU5.3 Bipin
Beam Angle (deg)	60
Beam Type	WFL
Bulb	MR16
Centerbeam Candlepower (cp)	350
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	3000
Diameter (in)	2.008
Diameter (mm)	51.00
Ecologic	YES
Family Brand Name	TRU-AIM TITAN®
Filament	AXIAL
Horizontal Beam Angle (deg)	60
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	45
Nominal Voltage (V)	12.00
Nominal Wattage (W)	20.00
Vertical Beam Angle (deg)	60



Footnotes
• Max. seal temperature 370 C (662F) • UV Filter capsule with axial filament in covered constant color, hard coated dichroic reflector. • Max pin temperature 220 C. • Max temperature at lens reflector joint 240 C. • Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.