

Project Name

Location

Prepared By



SATCO S13184

23W/LED/HID/ED23.5/840/E26/CL

Notes

(www) 04-10-2023 01:00:13

General

Status	Active
Watts	23W
HID Equivalent	100W
Volts	120V-277V
Shape	ED23.5
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	4000L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 5.98 in. Width: 5.98 in. Height: 10.16 in.
Ballasting Requirements	Ballast Bypass

Electrical

Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to +65C (+149F)

Physical

MOL	7.6
MOD	2.95
Housing Color	White
Weight (lb.)	0.3

Additional Information

Rated For Enclosed Fixture	Yes
IP Rating	IP65
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Year Limited - Hi-Pro

Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Wet
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp